Specifications

Eaton 138374



Catalog Number: 138374

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Clamp terminal 35-150mm², for 12x5-20x10

General specifications

Product Name	**Catalog Number**
Eaton xEffect SASY 60i busbar terminal	138374
EAN	**Product Length/Depth**
4015081351541	62 mm
Product Height	**Product Width**
51 mm	38 mm
Product Weight	**Compliances**
0.102 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

12 mm x 5/10 mm rail
20 mm x 5/10 mm rail
185 mm system
Compact system
Connection
60 mm system

Special features

Termination to busbars without drilling
A cable block is used to connect the conductor to the busbar

Type

185 mm system
60 mm system
Compact system
Connection

Width clamp

38 mm

Busbar thickness - max

10 mm

Busbar thickness - min

5 mm

Busbar width - max

20 mm

Busbar width - min

12 mm

Conductor cross section - max

150 mm²

Rated operational current (Ie) - max

480 A

Functions

Connections
Clamp terminal

Rated operation current (Ie)

480 A

Resources

Brochures

eaton-xeffect-sasy60i-customer-success-story-css-wagner-mueller-en-us.pdf

Catalogs

eaton-xeffect-sasy-60i-fk4300-1167gb-en-us.pdf

Product Range Catalog Switching and protecting motors

Certification reports

eaton-xeffect-sasy-60i-declaration-of-conformity.pdf

Drawings

eaton-control-panels-xeffect-sasy-clamp-terminal-3d-drawing.eps

Suitable for

Sector conductor connection

Round conductor connection

Flat rail

Strip conductor connection

Rated operational current

480 A

Terminal capacity (conductor)

35 mm² - 150 mm²

AWG2/0 - MCM300

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia