306D - Click wrenches without accessories



Standards:

NF EN ISO 6789, ISO 6789, DIN EN ISO 6789

Description:

- Factory accuracy: ± 2% except: - R.306-25D - K.306A600 - K.306A1000 (± 4%). - R.304DA (± 6%).
- Reliability of mechanism: 50 000 cycles (wrenches up to 200 N.m).
- Use possible with accessories: - End fitting: 9 x 12 or 14 x 18 mm. - Diameter: 30 mm.
- One-way wrenches usable for unscrewing by reversing the bits.
- Numbered wrenches supplied with ISO 6789 calibration certificate.
- Supplied in plastic box.

© FACOM 2020

	Length L [mm]	Attachement ["]	Capacity [Nm]	Graduation [Nm]	Weight [Kg]
J.306-50D	357.0	9 x 12	10 - 50	1.0	0.93
K.306-1000D	1280.0	Ø 30 mm	200 - 1000	4.0	5.9
K.306-600D	945.0	14 x 18	120 - 600	2.0	4.6
R.304DA	185.0	9 x 12	1 - 5	0.05	0.29
R.306-25D	271.0	9 x 12	5 - 25	0.1	0.45
S.306-100D	437.0	9 x 12	20 - 100	1.0	1.0
S.306-200D	515.0	14 x 18	40 - 200	1.0	1.3
S.306-350D	725.0	14 x 18	70 - 350	2.0	1.83

© FACOM 2020