

Extremely thin and soft with touchscreen function, superior for any work with sharp and small objects.

TEGERA® 8845

Learn more

A VERY, VERY THIN CUT F GLOVE

Extremely thin and soft cut protection glove (cut F) with touchscreen function made with the new advanced CRF®Omni technology, nylon and elastane. 18 gg knitted glove and PU-dipped, superior for any work with very sharp and small objects. Reinforcement between the thumb and index finger and touchscreen functionality. The new CRF® Omni technology does not contain any steel or glass fiber that can irritate the skin. The gloves stay soft and comfortable throughout the work task.

CHARACTERISTICS

- Highest level of protection
- Good grip
- Extra comfortable
- Durable
- Extremely good fingertip sensitivity
- Extra flexible

FUNCTIONS

- For touchscreen
- Soft
- Reinforcement between index finger and thumb
- Ultra thin

CRF® omni

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Cut injuries, abrasion injuries, scratches, lacerations, contact with dirt, contact with moisture

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dry environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Assembly, building and construction, metalwork, paper industry work, sheet-metal work

PRIMARY INDUSTRIES OF USE

Pulp and paper, metal fabrication, automotive

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Cut resistant gloves
CATEGORY Cat. II
LINING MATERIAL 18 gg, CRF® Omni Technology, HPPE, Nylon, Spandex
LENGTH 210-270 mm
DEXTERITY 5
GRIP DESIGN Smooth finish
COLOUR Black, Green, Grey
PAIRS PER: BUNDLE/CARTON 6/120
DISPLAY TYPE Bulk pack
DIPPING Palm-dipped
DIPPING MATERIAL PU
CUFF STYLE Knitwrist cuff
CUFF MATERIAL Textile
CUT RESISTANCE (EN ISO 13997) Cut resistance level F
CUT RESISTANCE (EN ISO 13997) TDM: 35.3 N
INNER MATERIAL SPECIFICATION HPPE (High performance polyethylene), Nylon, Tungsten fibre thread, Elastane
OUTER MATERIAL SPECIFICATION Polyurethane

COMPLIANCE

CE Cat. II

UKCA Cat. II

EAC

TP TC 019:2011

Information/UIS

EN 388:2016+A1:2018 3X43F

EN ISO 21420:2020

ANSI A7 CUT

ANSI 3 ABR

FEATURES

Cut protection

For touchscreen

SIZE		ARTICLE NUMBER	EAN
5	XXS	8845-5	7340118412597
6	XS	8845-6	7340118412740
7	S	8845-7	7340118412894
8	M	8845-8	7340118413044
9	L	8845-9	7340118413198
10	XL	8845-10	7340118413341
11	XXL	8845-11	7340118413495

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.