Date: 22/04/2024

PCS2TA 0,2 … 1,2 bar 1/4 NPT-F, 1/2 -14 NPT-F

Compact Pressure Switch

Item number: 48791184

Quantity: 1 pcs.

Order code: PCS2TA-BABC-1ASZZZZZZ ZCKW
M050000DZZZZZZZZ

Overview:
PCS2TA 0,2 … 1,2 bar 1/4 NPT-F, 1/2 -14 NPT-F
Compact Pressure Switch
PCS
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Diaphragm PTFE
Connection: Stainless steel AISI 316L
contact version: 1xSPDT, silver contact
Setting range, working range, proof pressure: 0,2 … 1,2 bar, working range 0 … 6 bar, proof pressure 10 bar
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case

Ingress Protection: IP66
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 33.30
Repeatability of set point: ≤ 1% of end of setting range

1. set point: 500.00 mbar decreasing,

Details:
Compact Pressure Switch
Model PCS
Specifications according to data sheet: PV 33.30
Repeatability of set point: ≤ 1% of end of setting range
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Diaphragm PTFE
1xSPDT, silver contact
0,2 … 1,2 bar, working range 0 … 6 bar, proof pressure 10 bar
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: without
Switch standard: without
Brand: WIKA Instruments Italia
Ingress Protection: IP66
PCS2TA 0,2 … 1,2 bar
1. set point: 500.00 mbar decreasing,

© 2024 - WIKA Instruments s.a.r.l.