MULTI-PURPOSE

SKYTEC OREGON

ULTRA LIGHTWEIGHT KNUCKLE COATED GLOVE WITH GREAT OIL GRIP

A very thin, flexible and dexterous knuckle coated glove offering outstanding tactility and grip in wet and oily conditions.

FEATURES

- Helps to protect the hand from oils, hydrocarbons, grease and abrasion to end of coated area
- Supple and soft 18 gauge nylon liner provides excellent fingertips sensitivity
- Nitrile sandy finish on palm offering excellent grip properties in wet and oily conditions
- Designed for easy movement and continuous wear
- Breathable back of hand to reduce perspiration
- Seamless knit prevents irritation
- Elasticated wrist provides a secure fit



LIGHTWEIGHT 18gg LINER

OIL GRIP

SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Engineering
- Manufacturing

Suitable Applications

- Handling oily components
- Maintenance
- Wet works
- Assembly

CERTIFICATION

CAT II

CE

EN 388:2016

4121X

See overleaf for explanation

Globus GROUP

MULTI-PURPOSE

SKYTEC OREGON

PRODUCT INFORMATION

MATERIALS	LINER:	Nylon
	COATING:	Nitrile sandy finish on smooth nitrile
COLOUR	Blue / black	
LENGTH (mm)	250 (Size Dependent)	
CUFF STYLE	Knitted	

RECOMMENDATIONS FOR USE

- USE: General handling glove with cut protection. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE : Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKG00002DD SKG00002DF SKG00002DH SKG00002DJ SKG00002DL	10 pairs per bag 120 pairs per case

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- P: Impact Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- 0-4: Puncture Resistance
- 0-4: Tear Resistance
- 0-5: Circular Blade Cut Resistance
- 0-4: Abrasion Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | SKY-DATA-OREGON-0320_1

EU compliance certificate delivered by the notified body ITS Testing Services UK Ltd, Centre Court, Meridian Business Park, Leicester, LE19 1WD, United Kingdom NB 0362

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.