Date: 12/04/2023

TCA2BA - 40 ... 100°C - 1/2 NPT male - Electrical connection: 1/2 -14 NPT-F

compact temperature switch

Item number: 48769495

Quantity: 1 pcs.

Order code: TCA2BA-CADC-EASZZZAB11Z ZCK
C006000IZZZZZZZZZ
F5-C5- - - - -

Overview:
TCA2BA - 40 ... 100°C - 1/2 NPT male - Electrical connection: 1/2 -14 NPT-F
compact temperature switch TCA
switch enclosure: aluminium,copper-free
sensor version: direct mounting
contact version: 1xSPDT, silver contact
setting range: 40 ... 100°C, working range -40 ... +120°C, proof temperature +140°C
Set point definition: Set Point customer-specifically configured
Process connection: 1/2 NPT male
Electrical connection: 1/2 -14 NPT-F
Mounting: standard direct or wall mounting, fixing bore on the case
Stem length for direct mounting: standard 125 mm
Sensor Dimensions: active length X = 65 mm, stem diameter D=9,5 mm
Brand: WIKA Instruments Italia
Ingress Protection: IP66
Specifications according to data sheet: TV 31.65
Repeatability of set point: ≤ 1% of span
1. set point: 60.00 °C increasing,

Approvals / Certificates
IECEx-ATEX Ex d

Details:
compact temperature switch
model TCA
Specifications according to data sheet: TV 31.65
Repeatability of set point: ≤ 1% of span
switch enclosure: aluminium,copper-free
sensor version: direct mounting
1xSPDT, silver contact
40 ... 100°C, working range -40 ... +120°C, proof temperature +140°C
Set Point customer-specifically configured
Process connection: 1/2 NPT male
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: with
Stem length for direct mounting: standard 125 mm

© 2023 - WIKA Instruments s.a.r.l.

Sensor Dimensions: active length X = 65 mm, stem diameter D=9,5 mm
Certificates: quality certificates
Brand: WIKA Instruments Italia
Ingress Protection: IP66
Unit: °C
TCA2B
1. set point: 60.00 °C increasing,

Approvals / Certificates
IECEx-ATEX Ex d

© 2023 - WIKA Instruments s.a.r.l.