ALPHA FLOW AMF-3CV

P3 DISPOSABLE RESPIRATOR

The Alpha Flow SERIES has been designed to improve comfort and performance whilst maintaining a secure fit. Colour coding the range makes identification simple and easy when varying levels of protection may be required.

FEATURES

- Large surface area ensures very low breathing resistance
- New large exhalation valve which reduces heat build-up and improves wearer comfort
- Colour coded alphamesh shell for ease of identification
- Adjustable headstrap allows for a secure and comfortable fit
- Metal-free - suitable for food industry applications
- Preformed nosebridge eliminates the need for regular adjustment
- Compatible with a wide range of safety eyewear
- Soft flexible mesh maintains it's shape and will not collapse during use
- Conforms to EN 149: 2001 + A1: 2009 FFP3 NR



PREFORMED NOSEBRIDGE
Ensures excellent fit without the need to keep adjusting while wearing



NEW LARGE EXHALATION VALVE
Reduces heat and moisture build-up



NEW MESH DESIGN
Lightweight, flexible and will not collapse during use



ORDERING INFORMATION

Part Number: AMF-3CV

Packaging: 10 singles per box
10 boxes per case

Certification: EN149: 2001 + A1: 2009
FFP3 NR

SUITABLE APPLICATIONS

Recommended applications include:

- **Craft Work**
- **Cutting and Casting of Metals**
- **Disposal of Toxic Waste**
- **Hospital**
- **Iron and Steel Industry**
- **Laboratory and Disease Control**
- **Manufacture of Batteries**
- **Mining**
- **Pharmaceutical industry**
- **Textile industry**
- **Underground Civil Engineering**
- **Woodworking**
- **Welding work**

ALPHA SOLWAY

ALPHA FLOW AMF-3CV

P3 DISPOSABLE RESPIRATOR

TECHNICAL SPECIFICATIONS

MATERIALS

COMPONENT	MATERIAL
Mesh Shell:	Polypropylene
Filter Outer Layer:	Polypropylene
Filter Inner Layer:	Polypropylene
Filter Internal Media:	Melt-Blown [Polypropylene]
Headstrap:	Woven Elastic [Latex-Free] Rubber
Headstrap Adjuster:	Polypropylene
Exhalation Valve - Valve Housing:	Polypropylene & ABS
Valve Membrane:	Synthetic Rubber
CV Pre-filter:	Activated Carbon Loaded Polypropylene
Inner Face Seal:	PVC Foam

DIMENSIONS

ITEM	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)
Respirator	155	70	125
Nosebridge	25	50	35
Headband	700	9	0.4
Headband clip	57	12	9
Valve	43	43	10

CERTIFICATION

EU Certification according to Regulation (EU) 2016/425 issued by: BSI Group, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes, MK5 8PP, United Kingdom. [N.B. No.0086].

RECOMMENDATIONS FOR USE

This respirator is disposable and recommended for single shift use only.

Do not attempt to clean or re-use.

PRODUCT SELECTOR GUIDANCE CHART

Approval EN 149: 2001 + A1:2009	Mesh Colour	Product Codes	APF (Assigned Protection Factor) (x WEL)	Non-Toxic Dusts	Fine / Toxic Dusts / Mists / Fumes	VeryFine / Toxic Dusts / Mists / Fumes	Odours/ Organic Vapours (Below WEL)	Metal Fumes	Oil/Water Based Particulates
FFP1 NR	White	AMF-1	4	■					■
FFP2 NR	Blue	AMF-2	10	O	■			O	■
FFP2 NR	Blue	AMF-2V	10	O	■			O	■
FFP3 R D ◢	Orange	AMF-3V	20	O	■	■		O	■
FFP3 NR ◢	Grey	AMF-3CV	20	O	■	■	■	■	■

■ = Recommended O = Alternative ◢ = Full Inner Face Seal

ALPHA-DATA-AMF3CV-0919

www.alphasolway.com **T: +44 (0)1461 202452** **E: alphasolway.sales@globusgroup.com**

ALPHA SOLWAY LTD, Factory 1, Queensberry Street, Annan, DG12 5BL, UK

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment.
The manufacturer reserves the right to make any modifications it deems necessary. © 2019 Alpha Solway Ltd

Part of Globus GROUP