
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	11/06/2019	DGUTTADAUR



SPECIFICATIONS:

IP RATING: 67 INDUSTRIAL (WHEN MATED)

MECHANICAL:

O-RING: RUBBER (NBR)
IP67 ADAPTER AND NUT: HIGH IMPACT FLAME RETARDANT PLASTIC
TEMPERATURE: -40°F TO 150°F (-40°C TO +68°C)

MISCELLANEOUS:

ALL DIMENSIONS ARE FOR REFERENCE ONLY.
COMPONENTS COME UN-ASSEMBLED AND SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES [mm]
OVERALL CABLE LENGTH TOLERANCE:
≤12 [305] = +1 [25] / -0
>12 [305] ≤60 [1524] = +2 [51] / -0
>60 [1524] ≤120 [3048] = +4 [102] / -0
>120 [3048] ≤300 [7620] = +6 [152] / -0
>300 [7620] = +5% / -0%
ALL OTHER DIMENSIONAL TOLERANCES:
.X = ± .2 [5]
.XX = ± .02 [.5]
.XXX = ± .005 [.13]

PROJECTION

APPROVALS	DATE
DRAWN BY DFRISIELLO	11/01/2019
CHECKED BY DGUTTADAUR	11/06/2019
APPROVED BY DGUTTADAUR	11/06/2019

CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY

COLOR VARIATIONS MAY OCCUR

L-com an INFINITE brand
50 HIGH STREET
NORTH ANDOVER, MA
01845

CATEGORY
TELECOM/MODULAR

PRODUCT DESCRIPTION
IP67 RJ45 PLUG KIT
COMPATIBLE W/ WP67-BHA-DC

SIZE	CAGE CODE	DWG. NO.	REV.
A	43321	WP67-RJ45-DC	A

SCALE: NONE SHEET 1 OF 1

L-com (OD) 2019