
# *Product datasheet*
*Characteristics*

# xzcp1241l5
pre-wired connectors XZ - elbowed female - M12 - 4 pins - cable PUR 5m



## Main

| | |
|---|---|
| Accessory / separate part category | Cabling accessories |
| Accessory / separate part type | Pre-wired connectors |
| Series name | General purpose |
| Electrical connection | Elbowed female connector M12, 4 pins |
| Collar material | Metal |
| Status LED | Without |
| Cable length | 5 m |

## Complementary

| | |
|---|---|
| Cable connector fixing | Screw-on |
| Cable outer diameter | 5.2 mm |
| Cable composition | 4 x 0.34 mm² |
| Wire insulation material | PUR |
| [Ue] rated operational voltage | 250 V AC<br>300 V DC |
| [In] rated current | 4 A |
| Contact resistance | <= 5000 µOhm |
| Insulating resistance | >= 1 GΩ |
| Product weight | 0.19 kg |

## Environment

| | |
|---|---|
| IP degree of protection | IP67 |
| Ambient air temperature for operation | -40...80 °C (static)<br>-5...80 °C (flexing) |
| Ambient air temperature for storage | -40...80 °C |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Not Green Premium product |
| RoHS | Compliant - since 0649 - Schneider Electric declaration of conformity |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.