Permanent Light 815 / Bulb

# Bulb 7W BA15D 48V



| Part No.: | 955.015.36 |
|---|---|

| MECHANICAL DATA | |
|---|---|
| Height | 54 mm |
| Diameter | 16 mm |
| Housing colour | Silver |
| Weight with packaging | 9 g |
| Product weight | 9 g |

| ELECTRICAL DATA | |
|---|---|
| Operating voltage | 48V |
| Operating voltage frequency | 50Hz |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 48 VAC |
| Rated operational current | 146 mA |
| Rated inrush current | 1.460 mA |
| Power illuminant | 7 W |

| OPTICAL DATA | |
|---|---|
| Lamp fitting/socket | BA15d |

| APPROVAL DATA | |
|---|---|
| Conforms with CE | No |
| WEEE | No |
| Conforms with RED directive | No |
| Conforms with ATEX-directive | No |
| Conforms with CCC | No |
| Conforms with FCC | No |
| Conforms with IC | No |
| EAC certificate available | No |
| Conforms with AS-I | No |
| ICAO Certification | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | No |

! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.