UGT507

UGB01200O1OG/US

Ultrasonic sensors



1: LEDs

Product characteristics		
Ultrasonic diffuse-reflection sensor		
Threaded type		
M18 x 1		
Connector		
Teach function		
Electrical data		
Electrical design		DC analogue
Operating voltage	[V]	10...30 DC
Current consumption	[mA]	< 35
Protection class		III
Reverse polarity protection		yes
Power-on delay time	[s]	0.1
Converter frequency	[kHz]	230
Inputs		
Teach		yes
Synchronisation		no
Multiplex		no
Outputs		
Output function		1x analogue 4...20 mA
Voltage drop	[V]	2.2
Short-circuit protection		yes
Overload protection		yes
Analogue output		
current output	[mA]	4...20
Max. load	[Ω]	500
Range		
Sensing range	[mm]	1200
blind zone	[mm]	80

UGT507

UGB01200O1OG/US

Ultrasonic sensors

Response curve		 1: Distance; 2: Sound beam; 3: Target 200 x 200 mm; 4: Target Ø 25 mm
Angle of aperture	[°]	8 ±2
Max. deviation from the 90° angle sensor / object	[°]	± 4
Accuracy / deviations		
Notes on the accuracy / deviation		The indicated values are reached after a warm-up time of ≥ 20 minutes
Temperature compensation		yes
Hysteresis	[%]	< 1
Switch-point drift	[%]	± 2.5
Linearity error	[%]	< 1
Resolution	[mm]	3
Repeatability	[%]	< 0.7
Environment		
Ambient temperature	[°C]	-20...70
Protection		IP 67
Tests / approvals		
EMC		EN 61000-4-2 ESD: 4 kV CD / plastics 8 kV AD / metal EN 61000-4-3 HF radiated: 3 V/m EN 61000-4-4 Burst: 2 kV EN 61000-4-6 HF conducted: 3 V EN 55011: class A
Vibration resistance		(10-55) Hz 1 mm amplitude, oscillation period 5 min., 30 min. per axis at resonance or 55 Hz EN 60068-2-6 Fc
Shock resistance		EN 60068-2-27 Ea yes
Mechanical data		
Housing materials		1.4404; polyamide; Epoxid-Glaskeramik
Weight	[kg]	0.095
Displays / operating elements		
Display		Switching status 1 LED yellow Echo LED 1 LED green
Electrical connection		
Connection		M12 connector
Wiring		

UGT507

UGB01200O1OG/US

Ultrasonic sensors





4: Teach

Accessories

Accessories (included)	2 fixing nuts, stainless steel; 2 washers, stainless steel

Remarks

Remarks	cULus - Class 2 source required
Pack quantity [piece]	1