Specifications

Eaton 121651

Catalog Number: 121651

Eaton Moeller® series C22 Indicator light, Flat, Screw connection, Lens Without lens, LED green, 230 V AC



General specifications

Product Name

Eaton Moeller® series C22 Indicator light 121651

Catalog Number

EAN

4015081194650

Product Length/Depth

56 mm

Product Height

30 mm

Product Width

30 mm

Product Weight

0.015 kg

Certifications

UL Listed
IEC/EN 60947-5-1
CE marking
UL File No.: E29184
VDE 0660
CSA certified
UL 508
CSA File No.: 165628
CSA-C22.2 No. 14-05 and 94-M91
CSA Class No.: 321103
UL Category Control No.: NKCR

Catalog Notes

Lenses for indicator lights →
accessories

Powering Business Worldwide

Product specifications

Type

Indicator lights

Product Category

RMQ Compact

Electric connection type

Screw connection

Fitted with:

Front ring

Light source

Pollution degree

3

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Connection to SmartWire-DT

No

Rated impulse withstand voltage (Uimp)

4000 V AC

Bezel color

Other

Lamp socket type

LED

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

-25 °C

Number of pilot lights

1

Opening diameter

22.5 mm

Opening height

0 mm

Rated insulation voltage (Ui)

250 V

Rated operational voltage (Ue) - max

230 V

Resources

Catalogs

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

Declarations of conformity

DA-DC-00004135.pdf

DA-DC-00004157.pdf

Drawings

eaton-operating-indication-c22-indicator-light-dimensions.eps

eaton-operating-button-symbol-004.eps

eaton-operating-c22-indicator-light-3d-drawing.eps

eCAD model

DA-CE-ETN.C22-L-XG-230

Installation instructions

eaton-rmq-titan-c22-pv-compact-program-emergency-buttons-instruction-leaflet-il04716025z.pdf

Installation videos

Eaton's RMQ compact solution pilot devices

mCAD model

eaton-c22-l-x-compact-3d-model.stp

DA-CD-leuchtmelder_ohne

DA-CS-leuchtmelder_ohne

eaton-c22-l-x-compact-drawing.dwg

Sales notes

eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf

System overview

Pilot devices - selection aid

Wiring diagrams

eaton-operating-c22-indicator-light-wiring-diagram.eps

Bezel material

Plastic

Degree of protection

NEMA 4X, 13

IP67/IP69K

Lens color

Without hood

Voltage type

AC

Design

Flat

Mounting position

As required

Light color

Green

Rated conditional short-circuit current (Iq)

1 kA

Rated operational voltage (Ue) - min

230 V

Width opening

0 mm

Overvoltage category

III

Lens type

Flat

Round

Terminal capacity

2 x (0.5 - 1.5) mm², flexible with ferrules to DIN 46228

2 x (0.5 - 1.5) mm², solid

Tightening torque

0.8 Nm, Screw terminals



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia