DATASHEET - NZM2-4-XKVI2POU-K

Jumper kit, +insulating plates, +heat sink, 4/2 p

Part no. **NZM2-4-XKVI2POU-K**
170119

General specifications	
Product name	Eaton Moeller series NZM link kit
Part no.	NZM2-4-XKVI2POU-K
EAN	4015081666164
Product Length/Depth	150 millimetre
Product height	94 millimetre
Product width	95 millimetre
Product weight	0.553 kilogram
Compliances	RoHS conform IEC
Product Tradename	NZM
Product Type	Accessories
Product Sub Type	Link kit
Delivery program	
Type	Accessory DC link kit Terminal
Number of poles	Two-pole
Amperage Rating	238 A (40 °C), 180 A (65 °C)
Special features	Jumper kit with IP2X cover and heat sink; incoming unit/outgoer on two sides
Frame	NZM2
Suitable for	Four-pole
Used with	N2-4-…-S1(-S15)-DC
Technical Data - Mechanical	
Special features	Jumper kit with IP2X cover and heat sink; incoming unit/outgoer on two sides
Design verification as per IEC/EN 61439	
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information	

Model			Other

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Wiring set for power circuit breaker (EC002050)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Wiring set for circuit breaker (ecl@ss13-27-37-04-24 [ACN957016])			
Suitable for number of poles			4
Model			Other

© 04/2023 by Eaton Industries GmbH