Date: 11/04/2023

F73.160/4, 0...120°C, L1=100 mmx8mm,

Gas actuated thermometer, stainless steel series

Item number:	48774545
Quantity:	1 pcs.
Order code:	F73.160-C1F-4ND-C0100-N05-4-Z-HZZ-ZZZZZZ G8 FZZZEVZZIWS-AZ1ZZZZZ2ZZZZ
Overview:	F73.160/4, 0...120°C, L1=100 mmx8mm, 1/2 NPT radial bottom Surface mounting bracket, die cast aluminium standard capillary stainless steel 1.4571 Capillary length: 5 m laminated safety glass class 1 per EN 13190 *WIKA* with Serial number
Details:	Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem material: stainless steel Model: F73.160, nominal size 160, with capillary Unit: °C Scale range: 0 °C ... 120 °C Connection design: 4, compression fitting, sliding on stem Process connection: 1/2 NPT Stem diameter: 8 mm Insertion length L1: 100 mm Capillary: standard capillary stainless steel 1.4571 Capillary length: 5 m Design of case mounting: Surface mounting bracket, die cast aluminium Ignition protection type: without Zone: without Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 Window: laminated safety glass Case: Stainless steel Connector location: radial bottom Manufacturer logo: *WIKA* Permissible ambient temperature: -40 … +60 °C with Serial number

© 2023 - WIKA Instruments s.a.r.l.