TEGERA®



Winter lined neoprene coated glove with chemical-, cut-, and heat protection.

TEGERA® 494

Learn more

HIGH SAFETY MULTI PROTECTION GLOVE

Winter lined neoprene coated glove with chemical-, cut-, and heat protection. 0,5 mm/19,6 mil. Crinkled grip pattern for extra grip. Withstands contact heat up to 500°C/932°F. High level of protection. Latex-free and extra-long.

CHARACTERISTICS

- High level of protection
- Good grip
- Warm

FUNCTIONS

- Extra long
- Waterproof
- Protection against chemicals
- Withstands contact heat up to 500°C
- Phthalate-free
- Latex-free

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Burn injuries, heat injuries, corrosive injuries, cut injuries, contact with chemicals, contact with moisture, contact with damp, contact with oil, contact with cold

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, cold environments, warm environments, moist environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Chemical technology work, chemical work, metalwork, mining, paper industry work, petro-chemical work

PRIMARY INDUSTRIES OF USE

Agriculture, oil, gas, petrochemical, pulp and paper, chemical, rubber and plastic, metal fabrication

TYPE OF WORK

Heavy weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves, Cold insulation gloves, Cut resistant gloves, Heat protection gloves
CATEGORY Cat. III
THICKNESS 0,5* mm (*chem-layer)
LINING Winter-lined
LENGTH 450 mm
GRIP DESIGN Crinkled grip pattern
COLOUR Black
PAIRS PER: BUNDLE/CARTON 6/36
AQL 0.65
DIPPING MATERIAL Neoprene
CUT RESISTANCE (EN ISO 13997) Cut resistance level C
INNER MATERIAL SPECIFICATION Cotton
OUTER MATERIAL SPECIFICATION Chloroprene

COMPLIANCE

CE 0598

UKCA Cat. III

EAC

TP TC 019:2011

Information/UIS

NOT FOR FATTY FOOD

EN ISO 374-1:2016/A1:2018 Type B
KLPT

EN ISO 374-5:2016

EN 407:2020
343343

EN 388:2016+A1:2018
3X22C

EN ISO 21420:2020

EN 511:2006
221

EN 511 cl. 5.2 Flexibility behavior (-20°C)

FEATURES

Cut protection

Warm lining

Waterproof

Windproof

Chemical protection

TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	K	L	P	T
Permeation level	6	2	6	6
Degradation %	8,8	15,5	8,8	1,0

SIZE		ARTICLE NUMBER	EAN
10	XL	494-10	7392626035577

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.