PRODUCT-DETAILS

UA63-30-11 230-240V 50Hz / 240-260V 60Hz

UA63-30-11 230-240V 50Hz / 240-260V 60Hz Contactor



General Information

Extended Product Type	UA63-30-11 230-240V 50Hz / 240-260V 60Hz
Product ID	1SBL371022R8811
EAN	3471522091888
Catalog Description	UA63-30-11 230-240V 50Hz / 240-260V 60Hz Contactor
Long Description	The UA63-30-11 230-240V 50Hz / 240-260V 60Hz is a 3-pole contactors for capacitor switching, can be used for the switching of capacitor banks whose inrush current peaks are less than or equal to 100 times nominal rms current. The table below gives the permissible powers according to operational voltage and temperature close to the contactor. It also specifies the maximum peak current Î values accepted by the contactor. The capacitors must be discharged (maximum residual voltage at terminals ≤ 50 V) before being re-energized when the contactors are making. In these conditions, electrical durability of contactors is equal to 100 000 operating cycles. The UA.. series 3-pole contactors are of the block type design. - Main poles and auxiliary contacts: 3 main poles, 2 built-in auxiliary contacts - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

© 2024 ABB. All rights reserved.

Popular Downloads

Data Sheet, Technical Information	1SBC101140C0203
Instructions and Manuals	FPTC407700P0003

Dimensions

Product Net Width	82 mm
Product Net Depth / Length	108 mm
Product Net Height	110 mm
Product Net Weight	1.2 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Standards	IEC/EN 60947-1, IEC/EN 60947-4-1
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-5-1, Θ = 40 °C 16 A
Rated Operational Power AC-6b (P_e)	(230 / 240 V) 40 °C, 50 / 60 Hz 25 kvar (230 / 240 V) 55 °C, 50 / 60 Hz 25 kvar (230 / 240 V) 70 °C, 50 / 60 Hz 21 kvar (400 / 415 V) 40 °C, 50 / 60 Hz 45 kvar (400 / 415 V) 70 °C, 50 / 60 Hz 37 kvar (400 / 415 V) 55 °C, 50 / 60 Hz 43 kvar (440 V) 40 °C, 50 / 60 Hz 50 kvar (440 V) 55 °C, 50 / 60 Hz 48 kvar (440 V) 70 °C, 50 / 60 Hz 41 kvar (500 / 550 V), 40 °C, 50 / 60 Hz 50 kvar (500 / 550 V) 55 °C, 50 / 60 Hz 50 kvar (500 / 550 V) 70 °C, 50 / 60 Hz 45 kvar (690 V) 40 °C, 50 / 60 Hz 70 kvar (690 V) 55 °C, 50 / 60 Hz 70 kvar (690 V) 70 °C, 50 / 60 Hz 60 kvar
Rated Operational Current AC-15 (I_e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A gG Type Fuses 1.5 ... 1.8 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 0.1 s 140 A for 1 s 100 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 440 V 1300 A cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 690 V 630 A
Rated Operational Current DC-13 (I_e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.30 A / 66 W (250 V) 0.3 / 75 W
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 1000 V acc. to IEC 60947-5-1 690 V

© 2024 ABB. All rights reserved.

	acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U_c)	50 Hz 230 ... 240 V 60 Hz 240 ... 260 V
Coil Consumption	Average Holding Value 50 / 60 Hz 18 V·A Average Pull-in Value 50 Hz 180 V·A Average Pull-in Value 60 Hz 180 V·A Holding at Max. Rated Control Circuit Voltage 50 Hz 18 V·A Holding at Max. Rated Control Circuit Voltage 50 Hz 5.5 W Holding at Max. Rated Control Circuit Voltage 60 Hz 18 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 5.5 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 180 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 210 V·A
Operate Time	Between Coil De-energization and NC Contact Closing 7 ... 14 ms Between Coil De-energization and NO Contact Opening 4 ... 11 ms Between Coil Energization and NO Contact Closing 8 ... 27 ms
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH75-25 (75 x 25 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied)	2 x M6 screws placed diagonally
Connecting Capacity Main Circuit	Flexible with Cable End 6 ... 16 mm² Rigid Cable 6 ... 25 mm²
Connecting Capacity Auxiliary Circuit	Flexible with Cable End 0.75 ... 2.5 mm² Rigid Cable 1 ... 4 mm²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Connecting Terminals (delivered in open position) Main Poles	M 6 (+,-) pozidriv 2 screws with 1x (13 x 10 mm) connector
Terminal Type	Screw Terminals

Environmental

Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air (0.85 ... 1.1 Uc) -40 ... +55 °C Near Contactor for Operation in Free Air (Uc) -40 ... 70 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	Without Derating 3000 m

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CB_FR2880_60002378
CCC Certificate	CCC 2008010304290409
CQC Certificate	CQC2018010304128276 CQC2008010304290409

© 2024 ABB. All rights reserved.

Declaration of Conformity - CCC	2020980304001623 2020980304001215
Declaration of Conformity - CE	1SBD250805U1000
Declaration of Conformity - UKCA	1SBD250822U1000
GOST Certificate	GOST_POCCFRME77B07175
UL Certificate	UL-US-L312527-1101-21215991-6 UL-CA-2139468-4
UL Listing Card	UL_E312527

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	140 mm
Package Level 1 Depth / Length	146 mm
Package Level 1 Height	96 mm
Package Level 1 Gross Weight	1.2 kg
Package Level 1 EAN	3471522091888
Package Level 2 Units	box 20 piece
Package Level 2 Width	503 mm
Package Level 2 Depth / Length	153 mm
Package Level 2 Height	307 mm
Package Level 2 Gross Weight	24 kg
Package Level 3 Units	160 piece

Classifications

Object Classification Code	Q
ETIM 7	EC001079 - Capacitor contactor
ETIM 8	EC001079 - Capacitor contactor
ETIM 9	EC001079 - Capacitor contactor
eClass	V11.0 : 27371006
UNSPSC	39121529

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → UA and UA..RA Contactors → UA63

© 2024 ABB. All rights reserved.



© 2024 ABB. All rights reserved.