powerbreaker protekt

IP66 Weatherproof Fused Timer Connection Unit - 7 Day

TECHNICAL DATA SHEET

PRO SERIES

FEATURES

- Can be used for long term projects in all weather conditions
- Weatherproof to IP66
- 1 or 2 hour 'Boost' & 'Advance' controls
- Ideal for control of: outdoor lighting, ponds, sprinkler systems
- 4 On & 4 Off settings per day, 700 hours battery back up
- Easy set - Day / 5 Day / 7 Day blocks



PSPT1G



Snap-Shut Clips
(Lift to Open)

TECHNICAL INFO

Product	PSPT1G
Description	Weatherproof Fused Connection Unit
Product Finish	Grey
Voltage	13A, 230V~240V 50Hz
Barcode	5012739644023
IP Rating	IP66
Display	Large Backlit DIsplay
Rated Impulse Voltage	4,000V
Operation	Integrated Control
Max Load	Resistive - 13A Inductive - 6A
Manual Switch Type	Double Pole Switch
Timer Switch Type	Relay (Single Pole)
Cord Anchorage	Cable Dia:4.6mm to 10.4mm
Terminal Capacity	Cable Size: 3 x 1.0mm² to 3 x 2.5mm
Knock Outs	20mm
Product Weight (nett)	502g
Packed Weight (gross)	578g
Product Dimensions	H137 x W132 x D80mm
Box Dimensions	H138 x W143 x D87mm
Guarantee	Timer 1 Year, Enclosure 5 Years
Timer Conforms to	BS1363-4, BS 5733:2010+A1:2014 BS EN 60730-1:2016+A1:2019 BS EN IEC 60730-2-7:2020
IP Box Conforms to	IEC 60670-1 & IEC 60670-22

GREEN BROOK
Tel: 01279 772 772
Email: info@greenbrook.co.uk
Web: www.greenbrook.co.uk