DATASHEET - SL7-CB-T-250

Base module;250 mm aluminum tube

Part no.	**SL7-CB-T-250**
	171453
EL Number (Norway)	**4137708**

Product name	Eaton Moeller® series SL7 Base module
Part no.	SL7-CB-T-250
EAN	4015081677825
Product Length/Depth	73 millimetre
Product height	367 millimetre
Product width	73 millimetre
Product weight	0.323 kilogram
Certifications	UL report applies to both US and Canada UL 508 Certified by UL for use in Canada CSA-C22.2 No. 94-91 UL CSA-C22.2 No. 14-10 IEC/EN 60947-5-1 CE UL File No.: E29184 UL Category Control No.: NKCR CSA Class No.: NKCR7 IEC/EN 60529
Product Tradename	SL7
Product Type	Base module
Product Sub Type	None
Color	Other
Fitted with:	Aluminum tube Banjo bolt Cover
Number of modules	Max. 5 (with standard base) Max. 5 Max. 10 (with base for mounting on both sides)
Connection to SmartWire-DT	No
Degree of protection	NEMA 4 IP66 NEMA 13 NEMA 4X
Mounting Method	Floor Bracket Horizontal Tube
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Rated impulse withstand voltage (Uimp)	4000 V AC
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Tube length	250 mm
Type	Base module
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	60 °C
Climatic proofing	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Terminal capacity (AWG)	24 - 14
Terminal capacity (flexible with ferrule and plastic collar)	0.25 - 1.5 mm^2

Terminal capacity (solid/flexible)		0.13 - 2.5 mm^2
Rated insulation voltage (Ui)		250 V
Rated operational voltage		230/240 V AC ± 10 % 24 V AC/DC ± 10 % 110/120 V AC ± 10 %

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Connection module for signal tower (EC001152)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, connection module (ecl@ss10.0.1-27-37-12-32 [AKF050014])

Connection type auxiliary circuit		Spring clamp connection
Suitable for tube mounting		Yes
Suitable for bracket mounting		Yes
Suitable for floor mounting		Yes
Colour		Other
Suitable for AS interface		No

© 04/2023 by Eaton Industries GmbH