Date: 24/01/2024

632.50.160 0 mbar...60 mbar G1/2B lower back mount

Capsule pressure gauge, process industry series

Item number: 9879568

Quantity: 1 pcs.

Order code: 632.50-F-MAEQZZ-GD-3ZZHZZZ-ZZZZZ TA3BFZZZ2DCAZ11MF DIAL-IAZ1ZZZZZZ11- ZZ3Z4ZZZZ LABEL-ASASZDE-

Overview:
632.50.160 0 mbar...60 mbar G1/2B lower back mount
Capsule pressure gauge, process industry series
laminated safety glass
Permissible ambient temperature: Standard
case with blow-out disc back
Case material: Stainless steel
class 1.6
IP 54
Single packing
EN 837-3 *WIKA*
Cl.1.6
Serial number *...*

Details:
Capsule pressure gauge, process industry series
Model: 632.50
Specifications according to data sheet: PM 06.03
Measuring system: stainless steel
Case: stainless steel
Bezel ring: cam ring (bayonet type), stainless steel
Movement: stainless steel
Case filling: without
Nominal size: 160 mm
Unit: mbar
Scale range: 0 mbar...60 mbar
Process connection: G 1/2 B
Connector location: lower back mount
Case type: case with blow-out disc back
Accuracy class: class 1.6
Movement: stainless steel
Ingress protection: IP 54
Package: Single packing
Case surface: bare
Pointer: standard pointer
Pointer colour: black
Permissible ambient temperature: Standard
Permissible medium temperature: Standard
Case material: Stainless steel

© 2024 - WIKA Instruments s.a.r.l.

Window: laminated safety glass
Dial description:
Pressure Gauge Standard: International (standard Europe)
color for 1.scale (outside): black
dial background: White
Manufacturer logo: *WIKA*
Serial number *...*
norm-mark on dial: *EN 837-3*
accuracy class on dial: *Cl.1.6*
inner packages label: Standard (with Wika Logo)
outside packages label: Standard (with Wika Logo)

© 2024 - WIKA Instruments s.a.r.l.