# PRODUCT DATASHEET
# LED PIN 40 300° 4.2W 827 Clear G9

LED PIN G9 | LED lamps with retrofit pin base G9




## Areas of application

- Atmospheric accent lighting throughout the home
- Shops, hotels and restaurants
- Outdoor use in suitable outdoor luminaires only

## Product benefits

- Good all-around light emission
- Long lifetime of up to 15,000 h
- Ideal for decorative and free-burning applications
- Three year guarantee

## Product features

- LED alternative to conventional high voltage lamps
- Good quality of light; color rendering index $R_a$: ≥ 80; constant chromaticity







© 2024, LEDVANCE GmbH. All rights reserved.

## TECHNICAL DATA


### Electrical data

| | |
|---|---|
| Nominal wattage | 4.2 W |
| Construction wattage | 4.20 W |
| Nominal voltage | 220…240 V |
| Operating mode | AC Mains |
| Claimed equiv. conventional lamp power | 40 W |
| Nominal current | 36 mA |
| Type of current | AC |
| Inrush current | 5.25 A |
| Operating frequency | 50/60 Hz |
| Mains frequency | 50/60 Hz |
| Max. lamp no. on circuit break. 10 A (B) | 30 |
| Max. lamp no. on circuit break. 16 A (B) | 39 |
| Total harmonic distortion | < 190 % |
| Power factor λ | > 0.40 |

### Photometrical data

| | |
|---|---|
| Luminous flux | 470 lm |
| Nominal useful luminous flux 90° | 470 lm |
| Luminous efficacy | 111 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Color rendering index Ra | ≥80 |
| Light color | 827 |
| Standard deviation of color matching | ≤6 sdcm |
| Rated LLMF at 6,000 h | 0.80 |
| Flickering metric (Pst LM) | 1.0 |
| Stroboscope effect metric (SVM) | 0.4 |


© 2024, LEDVANCE GmbH. All rights reserved.




## Light technical data

| | |
|---|---|
| Beam angle | 300 ° |
| Warm-up time (60 %) | ‹ 0.50 s |
| Starting time | < 0.5 s |

## Dimensions & Weight

| | |
|---|---|
| Overall length | 52.00 mm |
| Diameter | 20,0 mm |
| Maximum diameter | 19 mm |
| Product weight | 9.00 g |

## Temperatures & operating conditions

| | |
|---|---|
| Ambient temperature range | -20…+40 °C |
| Maximum temperature at tc test point | 73 °C |

## Lifespan

| | |
|---|---|
| Lifespan L70/B50 at 25 °C | 15000 h |
| Number of switching cycles | 100000 |
| Lumen maintenance at end of service lifetime | 0.70 |
| Rated lamp survival factor at 6,000 h | ≥ 0.90 |

## Additional product data


© 2024, LEDVANCE GmbH. All rights reserved.

| | |
|---|---|
| Base (standard designation) | G9 |
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Clear |
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

## Capabilities

| | |
|---|---|
| Dimmable | No |

## Certificates & Standards

| | |
|---|---|
| Energy efficiency class | E [1)] |
| Energy consumption | 5.00 kWh/1000h |
| Type of protection | IP20 |
| Standards | CE / EAC |
| Photobiological safety group acc. to EN62778 | RG1 |

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

## Country-specific categorizations

| | |
|---|---|
| Order reference | LEDPIN40 CL 4,2 |

## LOGISTICAL DATA

| | |
|---|---|
| Temperature range at storage | -20...+80 °C |

## Energy labelling regulation data acc EU 2019/2015

| | |
|---|---|
| Lighting technology used | LED |
| Non-directional or directional | NDLS |
| Mains or non-mains | MLS |
| Light source cap-type (or other electric interface) | G9 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |


© 2024, LEDVANCE GmbH. All rights reserved.

| | |
|---|---|
| Standby power | 0.00 |
| Networked standby power for CLS | 0 W |
| Claim of equivalent power | Yes |
| Length | 52.00 mm |
| Height | 20,0 mm |
| Width | 20,0 mm |
| Chromaticity coordinate x | 0.458 |
| Chromaticity coordinate y | 0.410 |
| R9 Colour rendering index | 0.00 |
| Beam angle correspondence | SPHERE_360 |
| Survival factor | 0.90 |
| Displacement factor | 0.5 |
| LED light source replaces a fluorescent light source | No |
| EPREL ID | 1403254,522877,1856544 |
| Model number | AC32126,AC24754,AC58909 |

## Safety advice

- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

## DOWNLOAD DATA

| | Documents and certificates |
|---|---|
| PDF | Declarations Of Conformity CE |

| | Photometric and lighting design files |
|---|---|
| | Spectral power distribution |

## LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---|---|---|---|---|
| 4058075449893 | Folding box<br>2 | 20 mm x 49 mm x 95 mm | 25.00 g | 0.09 $dm^3$ |
| 4058075626386 | Shipping box<br>12 | 109 mm x 79 mm x 104 mm | 182.00 g | 0.90 $dm^3$ |


© 2024, LEDVANCE GmbH. All rights reserved.

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---|---|---|---|---|
| 4058075449916 | Shipping box<br>160 | | | |
| 4058075626393 | Shipping box<br>96 | 236 mm x 176 mm x 237 mm | 1778.00 g | 9.84 $dm^3$ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- For dimming conformity see www.ledvance.com/dim
- For Guarantee see www.ledvance.com/guarantee

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.


© 2024, LEDVANCE GmbH. All rights reserved.