PSL112024

DIN RAIL SWITCHING POWER SUPPLY, SINGLE PHASE. 24VDC, 5A / 120W



Product designation			Switching power supplies
Product type designation			PSL1
Input characteristics			
Input type			Single phase
Rated supply voltage AC		VAC	Self-configurable 115…230
Operating range		V	90…132VAC - 180…264VAC / 210…375VDC
Rated frequency		Hz	50/60
Operational frequency			
	min	Hz	47
	max	Hz	63
Current consumption Max		mA	2.8A (90VAC) / 1.4A (180VAC)
PFC			0.7
Insulation voltage Input/Output			
	AC	VAC	3000
	DC	VAC	4242
Internal fuse (250VAC)			T3 15A 250VAC
Output characteristics			
Rated output voltage DC		VDC	24
Voltage trimming (potentiometer) DC			
	min	VDC	22.5
	Max	VDC	28.5
Rated output current		A	5
Rated output power		W	120
Temperature coefficient		%/°C	±0.03
Line adjustment		%	±0.5
Load adjustment		%	±1
Efficency		%	86
Overload protection			110…145%
Short-circuit protection			Fold forward
Ripple & noise		mV	50
Parallel connection		N°	3
Indications			
LED indicator for power on			Yes
LED indicator for low voltage			Yes
Power Rdy (Ready - minimum limit)			Yes
Connections			
Terminals type			Screw
Ambient conditions			
Temperature			
Operating temperature			

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

PSL112024

DIN RAIL SWITCHING POWER SUPPLY, SINGLE PHASE. 24VDC, 5A / 120W

		min	°C	-35
		max	°C	+71
	Storage temperature			
		min	°C	-40
		max	°C	+85
Derating			%/°C	2.5%/°C above 60°C

Housing

Material			Metal
IEC degree of protection			IP20
Dimensions (W x H x D)		mm	64 x 124.5 x 123.6
Weight		g	1018

Installations

Mounting			On 35mm DIN rail

Dimensions



TYPE	A	B	C
PSL1 120...	64 (2.52")	124.5 (4.90")	123.6 (4.87")
PSL1 240...	83.5 (3.29")	124.5 (4.90")	123.6 (4.87")
PSL1 300...	83.5 (3.29")	124.5 (4.90")	123.6 (4.87")
PSL1 480...	175.5 (6.91")	124.5 (4.90")	123.6 (4.87")
PSL3 120 24	74.3 (2.92")	124 (4.88")	118.8 (4.68")
PSL3 240...	89 (3.50")	124 (4.88")	118.8 (4.68")
PSL3 480...	150 (5.90")	124 (4.88")	118.8 (4.68")
PSL3 960...	275.8 (10.86")	125.9 (4.96")	120.3 (4.74")

Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n°14
IEC/EN 60950-1
IEC/EN 61000-6-2
IEC/EN 61000-6-3
UL 508

Certificates

cULus
EAC
RCM

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding