Date: 10/04/2023

S5550/4, NS100, 0...200°C, L1=518 x6mm

Bimetal thermometer, stainless steel version

Item number:	48754717
Quantity:	1 pcs.
Order code:	S5550 -4-C1L-GD-B518HZZ-AHAZZZZ TB FZZZEZSVID-AZ1ZZZZZ1ZZZZ
Overview:	S5550/4, NS100, 0...200°C, L1=518 x6mm Process connection: G 1/2 B laminated safety glass, Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) *WIKA* Serial number *...*
Details:	Bimetal thermometer, stainless steel version Specifications according to data sheet: TM 55.01 Case: stainless steel Stem material: stainless steel Model: S 5550, nominal size 100, adjustable stem and dial Accuracy class: class 1 per EN 13190 Connection design: 4, compression fitting, sliding on stem Unit: °C Scale range: 0 °C ... 200 °C Process connection: G 1/2 B Stem diameter: 6 mm Insertion length L1: 518 mm Window: laminated safety glass Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Case: Stainless steel Version: standard Stem material: stainless steel Ingress protection: IP 65 Permissible ambient temperature: -40 ... +70 °C Manufacturer logo: *WIKA* serial number on dial: Serial number *...* Explosion protection: ATEX Ignition protection type: Ex h

© 2023 - WIKA Instruments s.a.r.l.