efectorISO

KF5001

KFA3040BBPKG/NI/US

Capacitive sensors



1: LED 4 x 90°
2: potentiometer

Made in Germany

Product characteristics		
Capacitive sensor		
Metal thread M12 x 1		
Connector		
Increased immunity to conducted radio frequency interference		
Sensing range 4 mm; adjustable 1...6 mm; [f] flush mountable		
Application		
Application		For position detection of dry bulk materials and liquids
Electrical data		
Electrical design		DC PNP
Operating voltage	[V]	10...36 DC; "supply class 2" to cULus.
Current consumption	[mA]	< 12
Protection class		III
Reverse polarity protection		yes
Outputs		
Output function		normally open
Voltage drop	[V]	< 2.5
Current rating	[mA]	100
Short-circuit protection		pulsed
Overload protection		yes
Switching frequency	[Hz]	50
Range		
Sensing range	[mm]	4, adjustable 1...6 mm
Real sensing range (Sr)	[mm]	4 ± 10 %
Accuracy / deviations		
Correction factors		water = 1 / glass approx. 0.6 / ceramics approx. 0.5 / PVC approx. 0.4
Hysteresis	[% of Sr]	1...15
Switch-point drift	[% of Sr]	-20...20
Environment		
Ambient temperature	[°C]	-25...70
Protection		IP 65
Tests / approvals		
EMC		IEC 60947-5-2: 2007
MTTF	[Years]	636
Mechanical data		
Mounting		flush mountable

efectorISO

KF5001

KFA3040BBPKG/NI/US

Capacitive sensors

Housing materials		stainless steel 316L / 1.4404; PEEK (polyether ether ketone)
Weight	[kg]	0.048
Displays / operating elements		
Output status indication	LED	yellow
Electrical connection		
Connection		M12 connector

Wiring





Accessories		
Accessories (included)		2 lock nuts
Remarks		
Pack quantity	[piece]	1