6998 - STUD BRANCH TEE POLYMER MALE BSPT SS EPDM SEAL



maximum working pressure	16 bar 2 MPa 232 psi
working temperature	-10 to 95 °C 14 to 203 °F 263 to 368 °K
vacuum capability	755 mm Hg
body	BIO-BASED POLYMER
sub-base	FDA CHEMICAL NICKEL PLATED BRASS
'O'-rings	EPDM
gripping ring	STAINLESS STEEL

• Convert to inch • Convert to oz • Reset Filters

Part Nb	ØD (MM)	C	E (mm)	F (mm)	ØG (mm)	H (mm)	L_2 (mm)	(kg)
	All	All	All	All	All	All	All	All
6998 04 10	4	G1/8	5	13	8.5	22	14	.009
6998 04 13	4	G1/4	5.5	16	8.5	22	14	.014
6998 04 19	4	M5x0,8	3.5	8	8.5	24	14	.006
6998 06 13	6	G1/4	5.5	16	10.5	29	16	.016
6998 06 19	6	M5x0,8	3.5	10	10.5	30	16	.009
6998 08 10	8	G1/8	4.5	13	13.5	38	23	.019
6998 10 13	10	G1/4	5.5	16	16	43	26.5	.032
6998 10 17	10	G3/8	5.5	20	16	43	26.5	.055
6998 10 21	10	G1/2	7.5	24	16	43	26.5	.051
6998 12 17	12	G3/8	5.5	20	19	45.5	31	.042
6998 12 21	12	G1/2	7	24	19	45.5	31	.049