Specifications

# Eaton 107799

## Catalog Number: 107799

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 32A, box terminals, H2-A32-BT-NA




### General specifications

**Product Name**
Eaton Moeller series NZM - Molded case circuit breaker

**Catalog Number**
107799

**EAN**
4015081074464

**Product Length/Depth**
149 mm

**Product Height**
195 mm

**Product Width**
105 mm

**Product Weight**
2.345 kg

**Compliances**
RoHS conform

**Certifications**
UL (File No. E31593)
IEC/EN 60947
CSA-C22.2 No. 5-09
CSA (File No. 22086)
UL (Category Control Number DIVQ)
UL/CSA
IEC 60947-2
Specially designed for North America
IEC
UL 489
UL listed
CSA (Class No. 1432-01)
CE marking
CSA certified

Powering Business Worldwide

## Product specifications

### Type

Circuit breaker

### Special features

Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)
Rated current = rated uninterrupted current: 32 A
Switches conform to UL/CSA as well as the IEC regulations. IEC switching performance values are contained on the rating plate.
Adjustable overload releases Ir

### Application

Branch circuits, feeder circuits
Use in unearthed supply systems at 690 V

### Amperage Rating

32 A

### Voltage rating

690 V - 690 V

### Circuit breaker frame type

NZM2

### Features

Motor drive optional
Protection unit

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

## Resources

### Brochures

eaton-digital-nzm-brochure-br013003en-en-us.pdf

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

### Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

### Characteristic curve

eaton-circuit-breaker-current-nzm-mccb-characteristic-curve-005.eps

eaton-circuit-breaker-nzm-mccb-characteristic-curve-040.eps

eaton-circuit-breaker-nzm-mccb-characteristic-curve-050.eps

### Drawings

eaton-circuit-breaker-switch-nzm-mccb-dimensions-017.eps

eaton-circuit-breaker-nzm-mccb-dimensions-019.eps

### Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

### mCAD model

DA-CS-nzm2_3p

DA-CD-nzm2_3p

### Technical data sheets

eaton-nzm-technical-information-sheet

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.7 Inscriptions

Meets the product standard's requirements.

### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

### 10.8 Connections for external conductors

Is the panel builder's responsibility.

### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

### Pollution degree

3

### Mounting Method

DIN rail (top hat rail) mounting optional

Fixed

Built-in device fixed built-in technique

### Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

### Equipment heat dissipation, current-dependent

9.65 W

### Utilization category

A (IEC/EN 60947-2)

### Isolation

500 V AC (between auxiliary contacts and main contacts)

300 V AC (between the auxiliary contacts)

### Ambient operating temperature - max

70 °C

### Ambient operating temperature - min

-25 °C

### Ambient storage temperature - max

70 °C

### Ambient storage temperature - min

-40 °C

### Low-voltage HBC fuse - max

355 A gG/gL

### Number of auxiliary contacts (change-over contacts)

0

### Number of auxiliary contacts (normally closed contacts)

0

Number of auxiliary contacts (normally open contacts)

0

Protection against direct contact

Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110

Degree of protection

IP20 (basic degree of protection, in the operating controls area)
IP20

Direction of incoming supply

As required

Electrical connection type of main circuit

Frame clamp

Lifespan, mechanical

20000 operations

Overvoltage category

III

Rated operational current

300 A (415 V AC-1, making and breaking capacity)
32 A (660-690 V AC-3, making and breaking capacity)
300 A (380/400 V AC-1, making and breaking capacity)
32 A (690 V AC -1, making and breaking capacity)

Degree of protection (IP), front side

IP40 (with insulating surround)
IP66 (with door coupling rotary handle)

Degree of protection (terminations)

IP00 (terminations, phase isolator and strip terminal)
IP10 (tunnel terminal)

Number of poles

Three-pole

Terminal capacity (copper strip)

Max. 10 segments of 16 mm x 0.8 mm at box terminal
Min. 2 segments of 9 mm x 0.8 mm at box terminal
Max. 10 segments of 16 mm x 0.8 mm at rear-side connection (punched)
Min. 2 segements of 16 mm x 0.8 mm at rear-side connection (punched)

Lifespan, electrical

6500 operations at 400 V AC-3
5000 operations at 690 V AC-3

7500 operations at 690 V AC-1

10000 operations at 400 V AC-1

6500 operations at 415 V AC-3

### Functions

System and cable protection

Current limiting circuit breaker

### Shock resistance

20 g (half-sinusoidal shock 20 ms)

### Position of connection for main current circuit

Front side

### Rated operational current for specified heat dissipation (In)

32 A

### Release system

Thermomagnetic release

### Short-circuit total breaktime

< 10 ms

### Rated short-time withstand current (t = 0.3 s)

1.9 kA

### Rated short-time withstand current (t = 1 s)

1.9 kA

### Short-circuit release non-delayed setting - max

350 A

### Short-circuit release non-delayed setting - min

350 A

### Terminal capacity (control cable)

14 mm² - 18 mm² (1x)

16 mm² - 18 mm² (2x)

### Terminal capacity (copper busbar)

Min. 16 mm x 5 mm direct at switch rear-side connection

Max. 20 mm x 5 mm direct at switch rear-side connection

M8 at rear-side screw connection

### Terminal capacity (copper solid conductor/cable)

6 mm² - 12 mm² (1x) at box terminal

6 mm² - 11 mm² (1x) direct at switch rear-side connection

16 mm² (1x) at tunnel terminal

### Terminal capacity (aluminum solid conductor/cable)

16 mm² (1x) at tunnel terminal

### Terminal capacity (copper stranded conductor/cable)

4 mm² - 350 mm² (1x) at box terminal

4 mm² - 3/0 mm² (1x) direct at switch rear-side connection

4 mm² - 350 mm² (1x) at tunnel terminal

### Handle type

Rocker lever

### Short delay current setting (Isd) - max

0 A

### Short delay current setting (Isd) - min

0 A

### Instantaneous current setting (Ii) - max

350 A

### Instantaneous current setting (Ii) - min

350 A

### Number of operations per hour - max

120

### Overload current setting (Ir) - max

32 A

### Overload current setting (Ir) - min

25 A

### Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 230 V, 50/60 Hz

150 kA

### Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz

150 kA

### Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 440 V, 50/60 Hz

130 kA

### Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz

37.5 kA

### Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz

5 kA

### Rated short-circuit making capacity Icm at 400/415 V, 50/60 Hz

330 kA

### Rated short-circuit making capacity Icm at 440 V, 50/60 Hz

286 kA

### Rated short-circuit making capacity Icm at 525 V, 50/60 Hz

105 kA

### Rated short-circuit making capacity Icm at 690 V, 50/60 Hz

40 kA

Standard terminals

Box terminal

Rated operating voltage Ue (UL) - max

600Y/347 V, 480 V

Rated short-circuit making capacity Icm at 240 V, 50/60 Hz

330 kA

Rated impulse withstand voltage (Uimp) at auxiliary contacts

6000 V

Rated impulse withstand voltage (Uimp) at main contacts

8000 V

Rated insulation voltage (Ui)

1000 V AC

---

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia