



SKF Adapter Block 226402

The adapter block SKF 226402 consists of a cast steel block to which a pressure gauge and high-pressure pipe can be connected. It comes with a floor support and a 90 degree connection nipple for the oil reservoir.

Technical data

Designation	226402
Maximum pressure	400 MPa *(58 000 psi)*
Pressure gauge connection	$G^1/_2$
Pressure pipe connection	$G^3/_4$
Weight	2,55 kg *(5.6 lb)*





For bearing mounting

SKF Mounting Fluid LHMF 300

SKF Mounting Fluid is suitable for use with SKF hydraulic equipment, including hydraulic pumps, HMV ..E nuts and oil injection tools. SKF LHMF 300 contains anti-corrosives which are non-aggressive to seal materials such as nitrile rubber, perbunan, leather and chrome leather, PTFE, and so on.



For bearing dismounting

SKF Dismounting Fluid LHDF 900

SKF Dismounting Fluid is suitable for use with SKF hydraulic equipment, including hydraulic pumps and oil injection tools. SKF LHDF 900 contains anti-corrosives which are non-aggressive to seal materials such as nitrile rubber, perbunan, leather and chrome leather, PTFE, and so on.

Technical data

Designation	LHDF 900/pack size	LHMF 300/pack size
Specific gravity	0,885	0,882
Flash point	202 °C *(395 °F)*	200 °C *(390 °F)*
Pour point	–28 °C *(–18 °F)*	–30 °C *(–22 °F)*
Viscosity at 20 °C *(68 °F)*	910 mm^2/s	300 mm^2/s
Viscosity at 40 °C *(104 °F)*	330 mm^2/s	116 mm^2/s
Viscosity at 100 °C *(212 °F)*	43 mm^2/s	17,5 mm^2/s
Viscosity index	180	160
Available pack size	5 and 205 litre	1, 5, 205 litre