
Nozzles for Polymer Blowguns

0690 01 Standard Nozzle



Nickel-plated brass



C	DN		G	L	L1	kg
M12x1.25	2.5	0690 01 00	15	31	9	0.024



- Versatile use
- Progressive and powerful air jet


327 Nl/min | 86 dBA | 23°

OSHA 1910.95 (b)
2003/10/EC directive:
Requirement to use ear protection
if exposure > 8 hours

0690 02 Safety Nozzle



Nickel-plated brass



C	DN		G	L	L1	kg
M12x1.25	2.5	0690 02 00	15	31	9	0.024



- Fluidised Powders
- Air screen effect
- Safety: avoids the nozzle becoming completely blocked


315 Nl/min | 83 dBA | 26°

OSHA 1910.95 (b)/1910.242 (b)
2003/10/EC directive:
Requirement to use ear protection
if exposure > 8 hours

0690 03 Straight Nozzle (Long)



Nickel-plated brass



C	DN		G	L	L1	kg
M12x1.25	2.5	0690 03 00	15	332	307	0.068



- Restricted Access
- Progressive and powerful air jet


386 Nl/min | 82 dBA | 21°

OSHA 1910.95 (b)
2003/10/EC directive:
Requirement to use ear protection
if exposure > 8 hours

0690 04 Safety Straight Nozzle (Short)



Nickel-plated brass



C	DN		G	L	L1	kg
M12x1.25	2.5	0690 04 00	15	102	77	0.033



- Restricted Access
- Air screen effect and directional jet
- Safety: avoids the nozzle becoming completely blocked


410 Nl/min | 82 dBA | 21°

OSHA 1910.242 (b)/ OSHA 1910.95 (b)
2003/10/EC directive:
Requirement to use ear protection
if exposure > 8 hours

0690 05 Angled Nozzle (Long)



Nickel-plated brass



C	DN		G	L	L1	kg
M12x1.25	2.5	0690 05 00	15	316	292	0.065



- Restricted or distant access
- Progressive and powerful air jet
- 360° rotation

354 Nl/min | 82 dBA | 21°

OSHA 1910.95 (b)
2003/10/EC directive:
Requirement to use ear protection
if exposure > 8 hours