506 UP Hybrid - In/Out G65

Code: 506UG.63.08.00



Frame mark (EU)

506U U 166 FT CE

Lens mark (EU)

2C-1.4/5-1.4 U 1 FT K N CE

Gasket mark (EU)

506U U 166 FT CE / U 175 -F 506UG U 166 FT CE

Frame technology

Hybrid, Nose pad set-up, Adjustment of temples in length, Adjustment of temples in inclination, Rubber Terminal

Conditions of use

Standard brightness, Low brightness, Indoor - Outdoor

Lens technology

Anti-Scratch + Anti-Fog (KN - Vanguard PLUS), In/Out G65

Lens color

Clear

Lens material

Polycarbonate

Frame color

Black/Green

Standards

EN166, EN170, EN172

Scale number

(2C-1.4), (5-1.4)

Mechanical resistance

Low energy impact (F)

Optional requirements

Resistance to surface damage by fine particles (K), Resistance to fogging of oculars (N), Protection against high speed particles at extreme temperatures -5°/+55° C (T)

Optical class

Optical class (1)

Weight

38g

>> https://www.univetsafety.com/en/products/safety/spectacles/506-up-hybrid/506-up-hybrid-in-out-g65/



01.

LENS WITH ANTI-FOG AND ANTI-SCRATCH ULTRA PERFORMING VANGUARD PLUS TREATMENT

02.

TEMPLES ADJUSTABLE IN INCLINATION

03.

SOFT-RUBBER GASKET

for a gentle support on the face

04.

PANORAMIC AND WRAPAROUND LENS

for a better side protection

05.

ADJUSTABLE ELASTIC BAND

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.

HEADQUARTERS

Univet S.r.l. Via Giovanni Prati 87 25086 Rezzato - Telephone 030 2499411 - Fax 030 2499430 - info@univetsafety.com
VAT. IT02506570163