SPECIFICATION DATA SHEET

REF **42785**

TYPE	EQUIPMENT TRANSFORMER (unenclosed, single phase transformer)	
RATED CHARACTERISTICS	Primary voltage :	230 / 400V
	Secondary volotage :	115/230V
	Nominal power :	40 VA
ELECTRICAL CHARACTERISTICS	Fréquency :	50/60Hz
	Class B insulation	
	Class I	
	Air-cooled separating transformer	
	Max load losses :	3,7 W
	Voltage drop :	15,6 % for cos Φ = 1
		12,6 % for cos Φ = 0,45
	Efficiency :	79% for cos Φ = 1
		62% for cos Φ = 0,45
	Ucc :	14,2 %
	Insultation voltage :	
		. between coils : 4470V
		. between primary and core : 2240V
	Transformer protection :	Fuse T 0,4A L for 115V / T 0,2A L for 230V
OTHER CHARACTERISTICS	Weight :	1,0 Kg
	Dimensions :	A = 84 mm
		B = 70 mm
		C = 98 mm
	Attachments :	F = 40 mm
		G = 86 mm
		ϕ = 4,5 mm
	Transformer	**in accordance with IEC/BS EN 61558-2-4**

Service Technique Brachy
Le 27/02/2008