DATASHEET - CMUC230/25-22



Similar to illustration

Installation contactor, 230 VAC/DC, 2N/C+2N/O, 25A

Part no. CMUC230/25-22
Catalog No. 137403

Powering Business Worldwide

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	25
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Equipment heat dissipation, current-dependent	P_{vid}	W	7.5
Static heat dissipation, non-current-dependent	P_{vs}	W	0
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature min.		°C	-40
Operating ambient temperature max.		°C	60
			0

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Installation contactor for distribution board (EC001653)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Installation contactor for distribution board (ecl@ss10.0.1-27-14-23-08 [AFZ820015])

Rated operating voltage		V	440 - 440
Rated operation current		A	25
Utility category			0
Rated excitation voltage		V	195.5 - 253
Voltage type (operating voltage)			AC/DC
Voltage type (excitation voltage)			AC/DC
Number of contacts as normally open contact			2
Number of contacts as normally closed contact			2
Max. incandescent lamp load		W	3000
Max. load fluorescent lamp		VA	1360
Max. load fluorescent lamp (Duo circuit)		VA	2552
Max. load fluorescent lamp (parallel compensated)		VA	1360
Slider for hand switch			No
Width in number of modular spacings			2
Built-in depth		mm	69.5
Additional equipment possible			Yes
With day/night function			No
Hum-free			Yes
Degree of protection (IP)			IP20

© 07/2022 by Eaton Industries GmbH