Description

Identnumber	00047730
Key	0290-A-12,0-AA-VA-GM84-240/50-10 * JF06+MT05
BSTALT	L-290-A-12,0-A-VA 1/2-240/50-F-000
Description	2/2-way-solenoid valve; servo assisted
Type (TYP)	0290 - 0290
Circuit function (WW)	A - 2/2-ways; normally closed
Orifice size (DN)	12,0 - 12mm (7/16")
Seal material (DWST)	AA - EPDM
Body material (WKST)	VA - stainless steel
Port connection (LTA)	GM84 - G1/2 threaded port
Voltage (SP)	240 - 240 volts
Frequency (FR)	50 - 50 Hz
Power consumption (LEIS)	10 - 10 watt
Variable Code 1 (VAR1) (132445)	JF06 - cable plug 2508-00-B-00-3 1-BCS * KB01
Variable Code 2 (VAR2)	MT05 - direct coupling
PRICING	
ListPrice-EU	219.00 EUR

Technical Data

PRESS. MAX. (BAR) (DRMAXBAR)	16
PRESS MAX. (PSI) (DRMAXPSI)	232
PRESS. MIN. (BAR) (DRMINBAR)	0
PRESS. MIN (PSI) (DRMINPSI)	0
KV-VALUE (M*3/H) (KV)	1.8
QNN-VALUE (L/MIN) (QNN)	1900
WEIGHT (KG) (MASSE)	1.00
FLUID TEMP. MAX. (DEGREE C) (MEDTEMPMAX)	120
FLUID TEMP. MIN. (DEGREE C) (MEDTEMPMIN)	-30
AMB. TEMP. MAX. (DEGREE C) (UMGTEMPMAX)	55
SWITCH-ON TIME(%) (ESDAUER)	100
OPENING TIME MAX. (MS) (TOEFFMAX)	250
OPENING TIME MIN. (MS) (TOEFFMIN)	100
CYCLING RATE (1/MIN) (SH)	
CLOSING TIME MAX. (MS) (TSCHLMAX)	2000
CLOSING TIME MIN. (MS) (TSCHLMIN)	700