Specifications

# Eaton 136123

## Catalog Number: 136123

Eaton Moeller® series E57 Proximity switch, E57 Premium+ Short-Series, 1 N/O, 2-wire, 40 - 250 V AC, 20 - 250 V DC, M30 x 1.5 mm, Sn= 15 mm, Non-flush, NPN/PNP, Stainless steel, 2 m connection cable



## General specifications

**Product Name**
Eaton Moeller® series E57 Proximity switch

**Catalog Number**
136123

**EAN**
4015081329168

**Product Length/Depth**
158.75 mm

**Product Height**
50.8 mm

**Product Width**
133.35 mm

**Product Weight**
0.32 kg

**Certifications**
IEC/EN 60947-5-2
UL Category Control No.: NRKH, NRKH7

CSA Class No.: 3211-03
CE
UL 508
CSA-C22.2 No. 14
UL File No.: E166051
CSA File No.: 50513
UL
CSA

Powering Business Worldwide

## Product specifications

### Type
Inductive sensor

### Electric connection type
Cable

### Enclosure material finishing
Other

### Actuation type
Metallic Target

### Enclosure material
Metal

### Enclosure type
Cylinder, screw-thread

### Category (EN 954-1)
B

### Explosion safety category for dust
None

### Explosion safety category for gas
None

### Safety performance level (EN ISO 13849-1)
None

### SIL (IEC 61508)
None

### Ambient operating temperature - max
70 °C

### Ambient operating temperature - min
-25 °C

### Diameter sensor
30 mm

### Number of contact energized outputs with signalling function
0

### Number of contacts (normally open contacts)
1

### Number of outputs (protected contact energized)
0

## Resources

### Brochures
eaton-sensors-brochure-br053001en-en-us.pdf

### Catalogs
Product Range Catalog Sensors – products, basic information, applications

### Declarations of conformity
DA-DC-00004656.pdf

DA-DC-00004651.pdf

### Drawings
1360DRW-93

### Installation instructions
IL05301003Z

### Multimedia
We make what matters

Number of outputs (protected semiconductor)

0

Number of outputs (semiconductor with signaling function)

1

Output current at protected output - max

0 mA

Rated control supply voltage (Us) at AC, 50 Hz - max

250 V

Voltage type

AC

Mounting method

Non-flush mounting

Material

Stainless steel

Connection type

2-wire

2 m connection cable

Installation type

Not flat

Degree of protection

IP67

NEMA 4X, 6, 13

Interface type

None

LED indicator

Status indication of Switching state: Red LED

Switch function type

Normally open contact

Load current

5 - 200 mA (Ie, 70 °C)

5 - 250 mA (Ie, at 25 °C)

Residual current

2 mA (through the load in the blocked state at 230 V AC and 24 V DC)

Shock resistance

30 g, Mechanical, Shock duration 11 ms

Switching frequency

20 Hz

Voltage rating - max

250 V

Width sensor

0 mm

Product category

E57 Premium+ Short-Series

Switching output type

PNP/NPN

Temperature drift of sn

10 %

Rated control supply voltage (Us) at AC, 50 Hz - min

20 V

Rated control supply voltage (Us) at AC, 60 Hz - max

250 V

Rated control supply voltage (Us) at AC, 60 Hz - min

20 V

Rated control supply voltage (Us) at DC - max

0 V

Rated control supply voltage (Us) at DC - min

0 V

Rated switching distance (Sn) - max

15 mm

Repeatability

3 %

Sensor height

0 mm

Sensor length

45 mm

Supply voltage - max

250 V

Supply voltage - min

20 V

Switching hysteresis of Sn

20 %

Voltage drop (Ud)

12 V




Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia