Date: 24/04/2023

233.30.063 10 bar 2nd scale psi G1/4B lower back mount

Bourdon Tube Pressure Gauges, Safety Pattern

Item number: 48793145

Quantity: 1 pcs.

Order code: 233.30-C-BG410P-GB-3FHZCZZ-ZZZ1ZZZ 313D4AZIYG0 Z2Z-ICZZZZZ121ZZ
CERT22-EF2D-AA- - - - - - - - - - -
CERT31-EF2D-AB- - - - - - - - - - -
LABEL-PG1DE-ZZZZZ

Overview: 233.30.063 10 bar 2nd scale psi G1/4B lower back mount
Measuring System 316 SS
Ingress protection: IP 65
class 1.6
front flange, polished SS
Window: laminated safety glass
Case filling fluid: glycerine
Permissible medium temperature: + 100 °C
Permissible ambient temperature: -20 … +60 °C
Pressure Gauge Standard: International (standard Europe)
2nd scale red
stop-pin at zero
WIKA
with Serial number
Test report 2.2 per EN 10204
Certificate Language: English and French
Certificate for: pressure gauge
Formal certificate: Manufactured according to state-of-the-art
Inspection certificate 3.1 per EN 10204
Certificate type: Inspection certificate acc. to DIN EN 10204 3.1
Certificate Language: English and French
Certificate for: pressure gauge
Accuracy: Calibration values listed
Label: WIKA standard without / with Tag-number

Details: Bourdon Tube Pressure Gauges, Safety Pattern
Series EN 837-1
Model: 233.30
Specifications according to data sheet: PM 02.04
Measuring system: stainless steel
Case filling: with
Nominal size: 063 mm
Measuring range: gauge pressure range
Scale range: 0...10 bar
2nd Scale or Special Scale: 2nd scale psi

© 2023 - WIKA Instruments s.a.r.l.

Process connection: G 1/4 B
Connector location: lower back mount
Mounting flange/bracket: front flange, polished SS
Window: laminated safety glass
Pointer: standard pointer
Accuracy class: class 1.6
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316 SS
Case filling fluid: glycerine
Ingress protection: IP 65
Permissible medium temperature: + 100 °C
Permissible ambient temperature: -20 … +60 °C
Movement: stainless steel
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
color for 2.scale (inside): red RAL 3020
Manufacturer logo: *WIKA*
stop pin on dial: at zero
with Serial number
Permissible ambient temperature: -20 … +60 °C
Test report 2.2 per EN 10204
Certificate Language: English and French
Certificate for: pressure gauge
Formal certificate: Manufactured according to state-of-the-art
Inspection certificate 3.1 per EN 10204
Certificate type: Inspection certificate acc. to DIN EN 10204 3.1
Certificate Language: English and French
Certificate for: pressure gauge
Accuracy: Calibration values listed

© 2023 - WIKA Instruments s.a.r.l.