Rittal – The System.

Faster – better – everywhere.



# PK 9514.000

# Polycarbonate enclosures PK

State: 1/2/2023 (Source: rittal.com/in-en)

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

# PK 9514.000 - Polycarbonate enclosures PK without knockouts

Wall-mounted enclosure of fibreglass-reinforced polycarbonate. Protection category IP 66. Covers feature quick-release fasteners for speedy maintenance. Self-extinguishing material for safety.

## Features

| | |
|---|---|
| Model No. | PK 9514.000 |
| Applications | Ambient temperature range: -35 °C...+80 °C<br>The specified temperatures may be limited by the installed equipment |
| Material | Enclosure: Fibreglass-reinforced polycarbonate<br>Cover grey: Fibreglass-reinforced polycarbonate, all-round foamed-in PU seal<br>Cover screws: Polyamide<br>Insulating bungs: Polyethylene |
| Colour | RAL 7035 |
| Supply includes | Enclosure with cover<br>Cover screws<br>Insulating bungs for wall mounting screws |
| Protection category NEMA | NEMA 4X |
| Protection category to IEC 60 529 | IP 66 |
| IK Code | IK08 |
| Dimensions | Width: 180 mm<br>Height: 110 mm<br>Depth: 90 mm |
| Cover version | grey |
| Operating temperature range | -35 °C...80 °C |
| Basic material | Polycarbonate |
| Packs of | 2 pc(s). |

© Rittal 2023

# Features

| | |
|---|---|
| Weight/pack | 0.886 kg |
| Copper weight (kg per piece) | 0 |
| Customs tariff number | 94037000 |
| EAN | 4028177139497 |
| ETIM 7.0 | EC000261 |
| ECLASS 8.0 | 27180101 |

# Approvals

| | |
|---|---|
| Approvals | C-UL<br>DNV-GL<br>GOST<br>UL |
| Explanations | Declaration of conformity |