Specifications

Eaton 20D27

Catalog Number: 20D27

Eaton Bussmann series low voltage D fuse, 500V, 20A, 50 kAIC, Non Indicating, fuse, Class C gL/gG, Time delay, Blue, Ceramic body



General specifications

Product Name
Eaton Bussmann series low voltage D fuse

Catalog Number
20D27

EAN
5027590467759

UPC
051712832335

Product Length/Depth
50 mm

Product Height
21.5 mm

Product Width
21.5 mm

Product Weight
29.64 g

Compliances
CE Marked
GoST-R
RoHS Compliant

Certifications
IEC 60269
VDE
DIN EN 60269-3 (VDE 0636 Part 30)
DIN EN 60269-1 (VDE 0636 Part 10)
DIN VDE 0636-301

Powering Business Worldwide

Product specifications

Type

fuse

Application

For domestic and general industrial applications

Amperage Rating

20 A

Fuse size

DII

Breaking capacity

50 kA

Construction size (fuse inserts)

DII

Rated voltage AC

500 V

Class

Class C gL/gG

Fuse type

D27 -Time delay

Accessory/spare part type

20GD27 Blue screw cap gauge piece

Utilization category

gL/gG (cable protection/equipment protection)

Color

Blue

Interrupt rating

50 kAIC

Fuse indicator

Non-indicating

Connection

Other

Construction

D2

Construction size

DII

Fuse shape

Resources

Brochures

eaton-bussmann-series-d-and-d0-fuses-product-aid-pa132014en-en-us.pdf

Catalogs

CA134002EN

Declarations of conformity

CE Bottle fuse-links, holders, carriers and accessories

UKCA Bottle fuse-links, holders, carriers and accessories

Sales notes

Product change notification PCN_BUR_00188

Bottle

Response time

Time-delay

Suitable for

E27/DII Fuse base

TFD27 Fuse base screw fixing

SFRD27 Fuse base DIN-Rail mount

TFRD27 Fuse base DIN-Rail mount

Material

White ceramic body

Release characteristic

Time-lag

Quantity

25

Voltage rating

500 V

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia