Technical Specifications

Antistatic Full Body Harness





Description:

Full body harness with webbing extensions and removable dorsal pad. Includes back and front anchorage.

References:

1015074 S/M
1015075 L/XL
1030510 XXL

Features:

Shoulder and leg straps:

Material:	45mm polyester webbing antistatic with steel threads in the webbing to ensure total conductibility
Breaking strength :	>2200 daN

D shaped Ring (dorsal) + integrated extension

Material:	stainless steel Ø 7mm
Breaking strength :	> 5000 daN

Buckles for shoulder straps :

Material:	aluminium alloy 45mm
Breaking strength:	> 850 daN

Automatic buckle for leg straps :

Material:	stainless steel & aluminium
Breaking strength:	> 900 daN

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com

Weight : 1.400 kg

Static test : > 15 KN

Temperature of use : -30°C to +50°C

EN 361

Conform to ATEX EN 13463-1(2001)

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com