Technical specifications

Quick activating Falcon 6 m webbing with fall indicator



Description :

6 M webbing self retracting lifeline with fall indicator.
Visual annual inspection authorized by a competent person following the instructions given by the special check list supplied with the device.

Reference : 1031140

Features :

- Webbing : Polyester aramid fiber (length 6 m/width : 17 mm)
- Housing : High impact resistant polyamide
- Swivel : stainless steel
- 2 karabiners 1008342 : ¼ turn Alu. / 18 mm
- Minimum fall clearance: 2.60 m
- Breaking strength : >1500 daN
- Standard : EN360: 2002

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com

QUICK ACTIVATING BRAKE MECHANISM

Ref	**1031140**
Length	6 m
Top connector	Karabiner ¼ turn alu
Bottom connector	Karabiner ¼ turn alu
weight	1355 g
Dimensions	520x145x70

Fall indicator not activated



Fall indicator Activated



LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com