Date: 25/01/2024

233.50.100 -1/+1.5 bar G1/2B lower back mount

Bourdon Tube Pressure Gauges, Stainless Steel

Item number: 9510303

Quantity: 1 pcs.

Order code: 233.50-E-BV325Z-GD-3ZHZCZZ-ZZZZZZZ 213D3GZIYG0 Z2Z-IZZZZZZ12ZZZ
LABEL-PG1DE-ZZZZZ

Overview:
233.50.100 -1/+1.5 bar G1/2B lower back mount
Measuring System 316L
Ingress protection: IP 65
class 1.0
Window: laminated safety glass
Case filling fluid: glycerine-water-mixture
Permissible ambient temperature: -20 … +60 °C
Permissible medium temperature: + 100 °C
Pressure Gauge Standard: International (standard Europe)
WIKA
with Serial number
Label: WIKA standard without / with Tag-number

Details:
Bourdon Tube Pressure Gauges, Stainless Steel
Series
Model: 233.50
Specifications according to data sheet: PM 02.02
Measuring system: stainless steel
Case filling: with
Nominal size: 100 mm
Scale range: -1...+1.5 bar
Process connection: G 1/2 B
Connector location: lower back mount
Window: laminated safety glass
Pointer: standard pointer
Accuracy class: class 1.0
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316L
Case filling fluid: glycerine-water-mixture
Ingress protection: IP 65
Permissible medium temperature: + 100 °C
Permissible ambient temperature: -20 … +60 °C
Movement: stainless steel
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)

© 2024 - WIKA Instruments s.a.r.l.

Date: 25/01/2024

Manufacturer logo: *WIKA*
with Serial number

© 2024 - WIKA Instruments s.a.r.l.