THOR S3

An Ci Wr SRC

Standard EN ISO 20345 : 2011

LEMAITRE
Safety since 1974



WATER RESISTANT

UTURN® lacing system
- quick lacing
- made of durable nylon
- precision and adjustment

Waterproof breathable membrane lining
- 100% waterproof, breathable and anti-bacterial
- optimal ventilation of the foot
- improved comfort
- full upper fitting

Size 35 to 49

Ref. **THORS30NR**

Product Highlights

- **Heavy duty boot available with men's and women's fit.**
- **Ankle protection by Lemaitre**, malleolus protection against side impacts.
- **2,0 mm thick high strengh leather** (against abrasion, tearing and puncture). Tongue with gusset to prevent any infiltration of dust / stones.
- **Scuffcap TPU injected**: extreme resistance at the front.
- **Memory Foam Titan insock for immediate and lasting comfort:** antibacterial properties, respects foot hygiene.
- **Protective toe-cap**: composite HDFC.
- **Puncture-resistant midsole:** high tenacity fabric "0" penetration.



TRAILIUM PU2D antistatic sole

- **4 mm studs** suitable for construction and heavy duty industry
- **Drainage channels for liquids and mud** to avoid any risk of aquaplaning
- **Lateral edges and 15mm raised heel:** reinforced grip on ladder rungs
- **Large bearing surface,** optimal stability
- **Arch support and heel cushioning:** MSD prevention

USAGE

- Civil engineering and Forestry works
- Logistics, automotive
- Shipyard, construction
- Petrochemistry, chemistry

DEVELOPED RESPECTING THE FOOT ANATOMY

FRENCH TRADEMARK

lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority

THOR S3

Standard EN ISO 20345 : 2011

Characteritics of the upper

- **Upper material:** smooth full grain water-repellent leather with anti-abrasion TPU scuffcap
- **Tongue/gusset:** water-repellent leather
- **Collar:** water-repellent leather
- **Lining:** imper-breathing membrane

Characteristics of the sole

- **Designation :** TRAILIUM PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
  forward flat slip: 0,34 (standard ≥ 0,32)
  forward heel slip: 0,31 (standard ≥ 0,28)
- **SRB Adhesion coefficient:**
  forward flat slip: 0,20 (standard ≥ 0,18)
  forward heel slip: 0,17 (standard ≥ 0,13)

VARIANT



Balder S3 SRC
BALDS30NR

Practical information

Women fitting 35-39	**Men fitting** 40-49
Weight of one shoe size 38: 683 g	Weight of one shoe size 42: 763 g
CERTIFICATION N° 0075/007/161/07/19/2226 EXT 25/03/21	**CERTIFICATION N° 0075/007/161/07/19/2226 EXT 26/03/21**

Packaging

size 35 to 39	**size 40 to 49**
shoebox 345 x 230 x 122 mm	**shoebox** 355 x 340 x 130 mm
carton 635 x 485 x 355 mm	**carton** 670 x 355 x 360 mm
10 shoeboxes per carton	**5 shoeboxes per carton**

Gencods

35	3237154404355	**43**	3237154404430
36	3237154404362	**44**	3237154404447
37	3237154404379	**45**	3237154404454
38	3237154404386	**46**	3237154404461
39	3237154404393	**47**	3237154404478
40	3237154404409	**48**	3237154404485
41	3237154404416	**49**	3237154404492
42	3237154404423		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear						
SBP	●	●				
S1	●		A	E	Fo	
S1P	●	●	A	E	Fo	
S2	●		A	E	Fo	Wru
S3	●	●	A	E	Fo	Wru

● 200 J toe-cap: protection of the forefoot against impact and crushing.

● Anti-perforation insert 1100 N: foot protection against perforation.

- **A** Anti-static footwear
- **E** Shock absorption at the heel
- **Fo** Fuel oil-resistant outsole
- **Wru** Water penetration and water absorption resistant upper
- ESD Electrostatic discharge
- **Ci** Insulation against cold
- **Hi** Insulation against heat
- **Hro** Outsole resistance to hot contact
- **Wr** Water resistant
- **An** Ankle protection

- **SRA** Slip-resistance on ceramic floors with detergent
- **SRB** Slip-resistance on steel floors with glycerol
- **SRC** = **SRA** + **SRB**

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE
Safety since 1974

DON_LS 04 TDS 0093
updated: 21/07/21

Member of SYNAMAP