PRODUCT-DETAILS

# S201M-Z0.5

# S201M-Z0.5 Miniature Circuit Breaker - 1P - Z - 0.5 A



## General Information

| | |
|---|---|
| Extended Product Type | S201M-Z0.5 |
| Product ID | 2CDS271001R0158 |
| EAN | 4016779599443 |
| Catalog Description | S201M-Z0.5 Miniature Circuit Breaker - 1P - Z - 0.5 A |
| Long Description | System pro M compact S200M miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 10 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200M comply with IEC/EN 60898-1 and IEC/EN 609 47-2, allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200M to save 50% space. |

## ABB EcoSolutions

| | |
|---|---|
| ABB EcoSolutions | Yes |
| EcoSolutions Profile | 9AKK108469A3798 |

## Circular Value

© 2024 ABB. All rights reserved.

| | |
|---|---|
| Circular Design Principles Recyclability Rate | Design for Closing Resource Loops - Standard EN45555 - 90.6 % |
| Offered with Extended Lifetime | Product Durability |
| Offered with Takeback Services | Take Back for Recycling |
| End of Life Instructions | 9AKK108468A3132 |

## Eco Transparency

| | |
|---|---|
| Environmental Product Declaration - EPD | 9AKK108467A7833 |

## Technical

| | |
|---|---|
| Standards | CSA 22.2 No. 235<br>IEC/EN 60947-2<br>UL 1077 |
| Tripping Characteristic | Z |
| Rated Operational Voltage | acc. to IEC 60898-1 230 V AC<br>acc. to IEC 60898-1 230 V<br>acc. to IEC 60947-2 230 V AC |
| Operational Voltage | Maximum (Incl. Tolerance) 253 V AC<br>Maximum (Incl. Tolerance) 72 V DC |
| Rated Insulation Voltage ($U_i$) | acc. to IEC/EN 60664-1 440 V |
| Rated Impulse Withstand Voltage ($U_{imp}$) | 4 kV<br>at 2000 m 5 kV<br>at Sea Level 6.2 kV |
| Input Voltage Type | AC/DC |
| Rated Current ($I_n$) | 0.5 A |
| Rated Short-Circuit Capacity | (AC) 10 kA<br>(DC) 10 kA<br>(230 V AC) 10 kA<br>(230 V) 10 kA<br>(400 V) 10 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ($I_{cu}$) | (133 V AC) 25 kA<br>(230 V AC) 15 kA<br>(230 V) 15 kA<br>(400 V) 15 kA |
| Rated Conditional Short-Circuit Current ($I_{nc}$) | (230 V) 15 kA |
| Rated Service Short-Circuit Breaking Capacity ($I_{cs}$) | (133 V AC) 18.8 kA<br>(230 V AC) 10 kA |
| Rated Frequency (f) | 50 / 60 Hz |
| Power Loss | 2.4 W<br>at Rated Operating Conditions per Pole 2.4 W |
| Power Supply Connection | Arbitrary |
| Contact Position Indication | Red ON / Green OFF |
| Energy Limiting Class | 3 |
| Mechanical Endurance | 20000 cycle |
| Number of Protected Poles | 1 |
| Number of Poles | 1 |
| Overvoltage Category | III |
| Tightening Torque | 2.8 N·m |
| Actuator Type | Toggle |
| Screw Terminal Type | Failsafe Bi-directional Cylinder-lift Terminal |
| Actuator Marking | I / O |
| Actuator Material | Insulation Group II, Black, Sealable |
| Housing Material | Insulation Group II, RAL 7035 |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| Mounting on DIN Rail | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Mounting Position | any |
| Recommended Screw Driver | Pozidriv 2 |
| Accessories Available | Yes |
| Connecting Capacity | Busbar 10 / 10 mm²<br>Flexible with Ferrule 0.75 ... 25 mm²<br>Flexible 0.75 ... 25 mm²<br>Flexible 0.75 ... 25 mm²<br>Rigid 0.75 ... 35 mm²<br>Rigid 0.75 ... 35 mm²<br>Stranded 0.75 ... 35 mm² |
| Installation Size | acc. to DIN 43880 1 |
| Terminal Type | Screw Terminals |

## Material Compliance

| | |
|---|---|
| RoHS Information | 2CDK400003K0203 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date | 20161001 |
| REACH Declaration | 9AKK108468A9644 |
| REACH Information | True - contains substances > 0.1 mass percentage |
| REACH Date | 20231212 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

## Environmental

| | |
|---|---|
| Ambient Air Temperature | Operation -25 ... +55 °C<br>Storage -40 ... +70 °C |
| Degree of Protection | IP20<br>IP40<br>Enclosure with Cover IP40 |
| Pollution Degree | 3 |
| Environmental Conditions | 28 cycles<br>with 55 °C / 90-96 %<br>and 25 °C / 95-100 % |
| Resistance to Vibrations | 20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz |
| Resistance to Shock acc. to IEC 60068-2-27 | 25g 2 shocks 13 ms |

## Technical UL/CSA

| | |
|---|---|
| Maximum Operating Voltage UL/CSA | 60 V DC<br>480Y / 277 V AC |
| Interrupting Rating acc. to UL1077 | (277 V AC) 6 kA<br>(480Y / 277 V AC) 6 kA<br>(60 V DC) 10 kA |
| Connecting Capacity UL/CSA | Busbar 14-8 AWG<br>Conductor 14-4 AWG |
| Tightening Torque UL/CSA | 18 in·lb |

## Dimensions

| | |
|---|---|
| Width in Number of Modular Spacings | 1.0 |
| Product Net Width | 17.5 mm |
| Product Net Height | 88 mm |
| Product Net Depth / | 69 mm |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| Length | |
| Product Net Weight | 0.125 kg |
| Pole Net Weight | 0.125 kg |
| Built-In Depth ($t_2$) | 69 mm |
| Dimension Diagram | 2CDC022007F0010 |

## Ordering

| | |
|---|---|
| Package Level 1 Units | carton 10 piece |
| Package Level 1 Gross Weight | 1.295 kg |

## Certificates and Declarations

| | |
|---|---|
| Declaration of Conformity - CE | 2CDK403001D0607 |
| Declaration of Conformity - UKCA | 9AKK108467A5053 |
| I²t Characteristic | 9AKK107992A5104 |
| Certification Agency | CSA<br>EN<br>IEC<br>UL |

## Installation

| | |
|---|---|
| Instructions and Manuals | 2CDS207104P0002 |

## Popular Downloads

| | |
|---|---|
| Data Sheet, Technical Information | 9AKK107046A0423 |
| I²t Characteristic | 9AKK107992A5104 |

## Classifications

| | |
|---|---|
| ETIM 8 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 9 | EC000042 - Miniature circuit breaker (MCB) |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Business |
| CN8 | 8536 20 10 |
| UNSPSC | 39121603 |
| eClass | V11.0 : 27141901 |
| IDEA Granular Category Code (IGCC) | 4897 >> Miniature circuit breakers |
| Object Classification Code | F |

## Accessories

© 2024 ABB. All rights reserved.

| Identifier | Description | Type | Quantity | Unit Of Measure |
|---|---|---|---|---|
| 2CDS200922R0001 | S2C-S/H6R Signal / Auxiliary Contact | S2C-S/H6R | 1 | piece |
| 2CDS200912R0001 | S2C-H6R Auxiliary Contact | S2C-H6R | 1 | piece |
| 2CDS200970R0031 | S2C-H01 Auxiliary Contact | S2C-H01 | 1 | piece |
| 2CDS200970R0032 | S2C-H10 Auxiliary Contact | S2C-H10 | 1 | piece |
| 2CDS200936R0001 | S2C-H11L Auxiliary Contact | S2C-H11L | 1 | piece |
| 2CDS200936R0002 | S2C-H20L Auxiliary Contact | S2C-H20L | 1 | piece |
| 2CDS200936R0003 | S2C-H02L Auxiliary Contact | S2C-H02L | 1 | piece |
| 2CDS200946R0001 | S2C-H6-11R Auxiliary Contact | S2C-H6-11R | 1 | piece |
| 2CDS200946R0002 | S2C-H6-20R Auxiliary Contact | S2C-H6-20R | 1 | piece |
| 2CDS200946R0003 | S2C-H6-02R Auxiliary Contact | S2C-H6-02R | 1 | piece |
| 2CDS200909R0001 | S2C-A1 Shunt Trip | S2C-A1 | 1 | piece |
| 2CDS200909R0002 | S2C-A2 Shunt Trip | S2C-A2 | 1 | piece |
| 2CSS200911R0001 | S2C-UA 12 DC Undervoltage Release | S2C-UA 12 DC | 1 | piece |
| 2CSS200911R0002 | S2C-UA 24 AC Undervoltage Release | S2C-UA 24 AC | 1 | piece |
| 2CSS200911R0003 | S2C-UA 48 AC Undervoltage Release | S2C-UA 48 AC | 1 | piece |
| 2CSS200911R0004 | S2C-UA 110 AC Undervoltage Release | S2C-UA 110 AC | 1 | piece |
| 2CSS200911R0005 | S2C-UA 230 AC Undervoltage Release | S2C-UA 230 AC | 1 | piece |
| 2CSS200911R0006 | S2C-UA 400 AC Undervoltage Release | S2C-UA 400 AC | 1 | piece |
| 2CSS200911R0007 | S2C-UA 24 DC Undervoltage Release | S2C-UA 24 DC | 1 | piece |
| 2CSS200911R0008 | S2C-UA 48 DC Undervoltage Release | S2C-UA 48 DC | 1 | piece |
| 2CSS200911R0009 | S2C-UA 110 DC Undervoltage Release | S2C-UA 110 DC | 1 | piece |
| 2CSS200911R0010 | S2C-UA 230 DC Undervoltage Release | S2C-UA 230 DC | 1 | piece |
| GHS2001901R0003 | S2C-DH Mechanical Accessories | S2C-DH | 1 | piece |
| 2CSS200998R0001 | S2C-BP Mechanical tripping device | S2C-BP | 1 | piece |
| 2CSS200999R0001 | S2C-EST Plug-in base | S2C-EST | 1 | piece |
| 2CDS200918R0001 | S2C-NT Hand Operated Neutral | S2C-NT | 1 | piece |
| 2CCA880100R0001 | CMS-100PS Sensor | CMS-100PS | 1 | piece |
| 2CCA880101R0001 | CMS-101PS Sensor | CMS-101PS | 1 | piece |
| 2CCA880102R0001 | CMS-102PS Sensor | CMS-102PS | 1 | piece |

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

© 2024 ABB. All rights reserved.







ABB Eco Solutions™

© 2024 ABB. All rights reserved.