Date: 25/01/2024

732.51.160 250 mbar 2 x G 1/4 female

Differential pressure gauge

Item number: 9082972

Quantity: 1 pcs.

Order code: 732.51-ZZ F-8MG225Z-AA-UDZZZA ZZ-ZZZZ 7A 3FCZ3DFHZ-IZZZZZZ12ZZZ

Overview:
732.51.160 250 mbar 2 x G 1/4 female
Connector location: lower mount
case: with pressure blowout disk
max. static pressure: 6 bar
Overpressure safety: 2,5 bar
class 1.6
venting of pressure chamber
Ingress protection: IP 54
Window: laminated safety glass
Permissible ambient temperature: -20...+60 °C
Permissible medium temperature: -20...+100 °C
Pressure Gauge Standard: International (standard Europe)
WIKA with Serial number

Details:
Differential pressure gauge
Process industry series
All wellded construction
Model: 732.51
Specifications according to data sheet: PM 07.05
Case: stainless steel
Bezel ring: stainless steel
Movement: stainless steel
Case filling: without
Nominal size: 160 mm
Scale range: 0...250 mbar
Process connection: 2 x G 1/4 female
Connector location: lower mount
Venting of pressure chamber/flushing connection: venting of pressure chamber
Permissible ambient temperature: -20...+60 °C
Permissible medium temperature: -20...+100 °C
Accuracy class: class 1.6
max. static pressure: 6 bar
Overpressure safety: 2,5 bar
Case material: Stainless steel 1.4301
Case surface: bare
Ingress protection: IP 54
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*

© 2024 - WIKA Instruments s.a.r.l.

Serial number: with Serial number
Window: laminated safety glass
case: with pressure blowout disk

© 2024 - WIKA Instruments s.a.r.l.