Specifications

Eaton EBV333TW1



Catalog Number: EBV333TW1

Eaton Bussmann series low voltage NH fuse base, Switch disconnector, low voltage, 630 A, AC 690 V, NH3, AC21B, 3P, IEC, 185 mm busbar, simultaneous switching, 2-V Terminals with double V-clamps

General specifications

Product Name
Eaton Bussmann series low voltage NH fuse base

Catalog Number
EBV333TW1

EAN
5027590335393

Product Length/Depth
195 mm

Product Height
675 mm

Product Width
110 mm

Product Weight
6694 g

Compliances
CE

Certifications
IEC/EN 60947-1
IEC 60947-3

Powering Business Worldwide

Product specifications

Type

Fuse accessory

Application

Transformer substations, industrial low voltage distribution boards, cable cabinets

Rated permanent current (Iu)

630 A

Conditioned rated short-circuit current Iq

0.08 kA

Double interrupting

No

Number of poles

Three-pole

Construction size (fuse inserts)

NH3

Distance

Between rail center: 185 mm

Electrical connection type of main circuit

Screw connection

Construction size

NH3

Fuse shape

Vertical

Release indication

None

Suitable for

NH3

Suitable for fuses

NH3

Mounting method

Busbar

Voltage rating

690

Electrical connection type

Screw connection

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

Declarations of conformity

UKCA fuse switch disconnectors, EBC, EBV and EBH series

CE fuse switch disconnectors, EBC, EBV and EBH series

Technical data sheets

10275 EBV Vertical fuse switch-disconnector

Technical service bulletins

10293 EBH Horizontal switch-disconnector

Model

Fuse switch disconnector

Rated operating voltage (Ue) at AC - max

690 V

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia