Chemical protection

# ALTO 415

Frequent contact | intermittent wear

## Fine touch for light chemical protection




CHEMICAL PROTECTION
**TYPE B**

| EN388 | EN ISO 374-1 | EN ISO 374-5 |
|---|---|---|
| 1011X | TYPE B KMT | |

| EN 421 | CATEGORY 3 | DEXTERITY |
|---|---|---|
| | 0334 | EN420: 5/5 |

## SPECIFIC ADVANTAGES

### Comfort

- Tactile sensitivity, due to the gloves reduced thickness
- Added comfort and absorption of perspiration, due to the cotton flock-lining

### Productivity

- Good grip, due to the non-slip embossing

### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

### Care for the environment

- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

## INDUSTRIES

- Automotive/mechanical industry
- Aeronautics industry
- Other industries

## APPLICATIONS

- Work with composite materials (resins)
- Industrial cleaning, maintenance
- Spray-painting

Edit 02/12/2024

Chemical protection

# ALTO 415

Frequent contact | intermittent wear

## LEGENDS

EN388



MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

| 1 | 0 | 1 | 1 | X | |
|---|---|---|---|---|---|
| 0-4 | 0-5 | 0-4 | 0-4 | A-F | P |

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 1: Abrasion resistance

EN ISO 374-1



TYPE B

CHEMICAL RISKS

K: Sodium hydroxide 40%
M: Nitric acid 65%
T: Formaldehyde 37%

EN 421



RADIOACTIVE CONTAMINATION

EN ISO 374-5



MICRO-ORGANISMS

Protection against bacteria and fungi

## PRODUCT DETAILS

| | |
|---|---|
| Interior finish | Flocked |
| Exterior finish | Embossed texture |
| Material | Polychloroprene and natural latex |
| Cuff characteristic | Straight cuff |
| Colour.s | Black |
| Length (cm) | 32 |
| Thickness (mm) | 0.6 |
| European sizes | 6 7 8 9 10 11 |
| Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity) | 6.5E+12 Ω |
| Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity) | 6.6E+12 Ω |

## LOGISTIC DETAILS

| | |
|---|---|
| Packaging | 1 pair/bag<br>10 pairs/bag<br>100 pairs/carton |

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1643
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 02/12/2024