DATASHEET - M22S-DDL-GR-GB1/GB0

Double actuator pushbutton, RMQ-Titan, Actuators and indicator lights non-flush, momentary, White lens, green, red, inscribed, Bezel: black, START/STOP

Part no. **M22S-DDL-GR-GB1/GB0**
216703

Product name	Eaton Moeller® series M22 Double actuator pushbutton
Part no.	M22S-DDL-GR-GB1/GB0
EAN	4015082167035
Product Length/Depth	30 millimetre
Product height	55 millimetre
Product width	30 millimetre
Product weight	0.015 kilogram
Certifications	CSA File No.: 012528 IEC/EN 60947-5 CSA Class No.: 3211-03 VDE 0660 UL 508 CSA-C22.2 No. 94-91 UL File No.: E29184 IEC/EN 60947 CE UL Category Control No.: NKCR CSA CSA-C22.2 No. 14-05 UL GL LR DNV
Product Tradename	M22
Product Type	Double actuator pushbutton
Product Sub Type	None
Bezel color	Black
Bezel material	Plastic
Design	Non-Flush Classical
Features	Labelled
Fitted with:	Front ring
Inscription	Inscribed
Lens color	White
Degree of protection	NEMA 3R IP66 NEMA 12 NEMA 13 NEMA 4X
Degree of protection (front side)	NEMA 4X IP66
Lifespan, mechanical	200,000 Operations
Opening diameter	22.5 mm
Operating frequency	3600 Operations/h
Product category	RMQ-Titan
Size	Front dimensions: 29,7 x 54,7 mm
Suitable for	Illumination
Type	Double actuator
Mounting position	As required
Shock resistance	30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27

Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			70 °C
Ambient storage temperature - min			40 °C
Ambient storage temperature - max			80 °C
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Connection to SmartWire-DT			Yes With SWD-RMQ connections
Actuating force			5 N
Actuator color			Green, red
Actuator function			Spring-return Momentary
Force for positive opening - min			0 N
Equipment heat dissipation, current-dependent Pvid			0 W
Heat dissipation capacity Pdiss			0 W
Heat dissipation per pole, current-dependent Pvid			0 W
Rated operational current for specified heat dissipation (In)			0 A
Static heat dissipation, non-current-dependent Pvs			0 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for push button (EC000221)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecl@ss10.0.1-27-37-12-10 [AKF028014])

Colour button			Red/green
Number of command positions			2
Construction type lens			Oval
Hole diameter		mm	22.5
Width opening		mm	0
Height opening		mm	0
Type of button			Flat

Suitable for illumination	Yes
With protective cover	No
Labelled	Yes
Switching function latching	No
Spring-return	Yes
With front ring	Yes
Material front ring	Plastic
Colour front ring	Black
Degree of protection (IP), front side	IP66
Degree of protection (NEMA), front side	4X

© 04/2023 by Eaton Industries GmbH