*Date: 11/04/2023*

# SC15.20.060 0 ... 60°C/°F CL.2

## Tension thermometer - Indicating temperature controller SC15

Item number: 48765214

Quantity: 1 pcs.

Order code: SC15-ZZ20060AB04DLF2AAZZZZZZZZZA0500Z19M0800140G3Z6
ZZZZZZZZ1ZZZZZZZB2CZ

Overview:
SC15.20.060 0 ... 60°C/°F CL.2
standard, steel case
Panel mounting with clamp, triangular front ring chrome plated,
2 adjustable changeover switches,
adjusting knob push in
5 A non-inductive at max. 250VAC 50/60Hz
terminal block
Capillary [FL]: 5.00 m Copper plastic covered,
Supportspiral (sensor)
Connection design: SV19 G3/8B
Insertion length [L1] o. [U1]: 140 x 8 mm brass
Dial background: White *WIKA*

Details:
Tension thermometer - Indicating temperature controller SC15
Specifications according to data sheet: TV 28.02
Model: SC15 - combistat
Design: standard, steel case
Nominal size [NG, d1]: 60 mm
Mounting option: Panel mounting with clamp,
Front ring: triangular front ring chrome plated,
Unit: Double scale °C/°F
Scale range: 0 ... 60°C/°F
Contact type: 2 adjustable changeover switches,
Contact adjustment: adjusting knob push in
Switch rating: 5 A non-inductive at max. 250VAC 50/60Hz
Cable connection: terminal block
Capillary material: Copper plastic covered,
Capillary [FL]: 5.00
Connection design: SF91/SV19 - Connection rotatable with lose connection,
Probe material: brass
Probe diameter [d5] o. [F1]: 8 mm
Insertion length [L1] o. [U1]: 140
Process connection [d6 o. E]: Male thread G3/8B
Manufacturer logo: *WIKA*
Accuracy class: class 2 per EN 13190
Capillary protection: Supportspiral (sensor)
Dial background: White

*© 2023 - WIKA Instruments s.a.r.l.*