Rittal – The System.

Faster – better – everywhere.

Roof-mounted fan, roof vent – SK 3138.000

Date : Apr 26, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Roof-mounted fan, roof vent – SK 3138.000

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Description:	Roof-mounted fan with a high protection category and flexible installation from the inside or outside.
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 21 without filter mat IP 55 including filter mat
Protection category NEMA:	NEMA 12
Supply includes:	Complete unit ready to install, including filter mat
Note:	To improve energy efficiency and extend the service life of the devices, we recommend the use of thermostats or temperature displays

Product description

Air throughput, unimpeded air flow (without filter mats):	
Air throughput, unimpeded air flow (with filter mats):	
Dimensions:	Width: 400 mm Height: 133 mm Depth: 400 mm
Required mounting cut-out:	Width: 258 mm Depth: 258 mm

Â© Rittal 2021

Installation depth:	27.5 mm
Temperature range:	Bearing: -40 °C...+70 °C Operation (environment): -20 °C...+55 °C
Fan:	without fan motor
eCl@ss 8.0/8.1:	27180716
Packs of:	1 pc(s).
Weight/pack:	3.2 kg
EAN:	4028177709188
Customs tariff number:	84213925
ETIM 7.0:	EC000320
ETIM 6.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 6.0/6.1:	27180716
Product description:	SK roof-mounted fan, roof vent, WHD: 400 x 133 x 400 mm, without fan motor

Approvals

Approvals:	Approval overview CSA UL + C-UL - FTTA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity