TECHNICAL DATA SHEET

RCD Fused Connection Unit - 30mA Passive

GREEN BROOK ELECTRICAL

PowerBreaker ProteKt

- Weatherproof to IP67
- Can be used for long term projects in all weather conditions
- Uses PowerBreaker technology
- Passive - Mechanically latched - does not need resetting after a power loss
- High intensity LED power on indicator
- Extra fast trip action - typically cuts the power less than 20mS
- Twin earth terminals

Type A RCD
BS 7288-2016



H92IP-X

	H92IP-X
Product Finish	White Unit / Grey Enclosure
Barcode	5012739600081
Product Weight	610g
Product Dimensions	W125 X H125 X D76mm
Voltage	10A, 230V AC ~ 50Hz
Max Operating Current	10A total load (complete with 10A fuse fitted)
IP Rating	IP67
Rated Trip Current	30mA
Typical Trip Speed	Less than 20mS (typical)
RCD Contact Break	Double Pole
Terminal Capacity	6mm² max
Rated Short Circuit Breaking & Making Capacity	250A
Rated Conditional Short-Circuit Current	1500A Power Factor Range .93 to .98
Latching	Mechanical - No need to reset after Power Loss (Passive)
Knockouts	6 x 20mm, 4 x 25mm
Main Housing	High Impact Polycarbonate
Guarantee	5 Years
Conforms To	BS 7288-2016 & BS EN60670

GREEN BROOK ELECTRICAL
Tel: 01279 772 772
Fax: 01279 422 007
Email: sales@greenbrook.co.uk
www.greenbrook.co.uk