SLIM LED TRI-PROOF - RADAR

LD2WPF453MW

45 W - 6600lm - 4000K





DIMENSIONS	A	B	C
1	78	80	1550

GENERAL INFORMATIONS	
Code	LD2WPF453MW
Ean	8031453027247
Family	SLIM LED TRI-PROOF - RADAR
Technology	LED
Variant	SENSORE A MICROONDE
Body material	PC
Diffuser / lens material	PC
Operating temperature (° C)	-20 - +40
Years warranty	5
External driver	SI

LIGHTING DATA	
Light colour	CW
CCT (K)	4000
Luminous)ux (lm)	6600
Luminous Flux Module (lm)	7200
Beam (°)	120
Luminous Efflcacy (lm/W)	166
Color rendering (CRI)	>80

TECHNICAL FEATURES	
Power (W)	45
Supply voltage (V) / Max (V)	220 / 240
Power frequency (Hz)	50/60
Insulation class	1
Power factor	>0,90
Dimmer compatibility	NO
Nominal life (h)	50000
Impact resistance (IK)	8

PACKAGING	
Packaging	BOX

Bot Lighting srl con unico socio
Via Lombardia, 37/39 – 30030 Cazzago di Pianiga (VE) Italy - T. +39.041.51.29.411 – F. +39.041.51.01.715
www.botlighting.it – ordini@botlighting.it – info@botlighting.it
NOTE: dati soggetti a modifiche senza preavviso | NOTE: data subject to change without notice

Release 4/11/2024

SLIM LED TRI-PROOF - RADAR

LD2WPF453MW

45W - 6600lm - 4000K

- Tri-proof in polycarbonate with stainless steel hooks
- Slim design
- High efficiency up to 140 lm/W
- Resistant to water, dust and corrosion
- Option version with microwave sensor programmable by dip-switch (sensitivity, ambient light level, light switch-on time)

