DATASHEET - S811+T18P3S

Soft starter, 180 A, 200 - 600 V AC, Us= 24 V DC, with control unit and pump algorithm, Frame size T

Part no.	**S811+T18P3S**
	168985
EL Number (Norway)	**4137469**

General specifications

Product name	Eaton S811 Soft starter
Part no.	S811+T18P3S
EAN	4015081654802
Product Length/Depth	164.4 millimetre
Product height	322.9 millimetre
Product width	194.4 millimetre
Product weight	18.6 kilogram
Compliances	CE Marked
Certifications	CCC CE UL IEC/EN 60947-4-2 C-Tick UL 508 CSA Class No.: 3211-06, 2411-01 UL File No.: E202571 CSA CSA File No.: LR 353 GB14048 CSA22.2-14-1995 UL Category Control No.: NMFT CSA-C22.2 No. 14 EN 60947-4-2 CSA file No. 3211-06 UL Listed UL Recognized CSA Certified for Elevator Duty IEC 60947-4-2
Product Tradename	S811
Product Type	Soft starter
Product Sub Type	None
Catalog Notes	Terminal blocks for the terminals are required for frame sizes T, U, and V -> Accessories Regulator supply: External supply voltage External solution required (reversing contactor)

Features & Functions

Fault memory	10 Faults
Fitted with:	Internal bypass Motor overload protection Internal bypass contacts Display
Functions	Single direction Underload monitoring Suppression of closing transients Potential isolation between power and control sections Current limitation Suppression of DC components for motors Soft start function Min. ramp time 1 s - fast switching (semiconductor contactor) Overload monitoring
Interfaces	Modbus RTU (built-in)

General information

Class	Adjustable
Connection to SmartWire-DT	No
Degree of protection	NEMA Other IP20
Frame size	T
Mains voltage - min	200 V
Mains voltage - max	600 V
Mounting position	As required

Overvoltage category	II
Pollution degree	3
Radio interference class	Class A (EN 55011)
Rated impulse withstand voltage (Uimp)	4000 V
Rated insulation voltage (Ui)	660 V
Shock resistance	15 g, Mechanical
Startup class	CLASS 20 (heavy starting duty 3 x I# for 45 s) CLASS 30 (6 x I# for 30 s) CLASS 10 (star-delta replacement)
Suitable for	Branch circuits, not as BCPD, (UL/CSA)
Type	Soft starter for three-phase loads, with control unit and pump algorithm
Used with	Three-phase motors
Voltage type	DC

Climatic environmental conditions

Altitude	Max. 2000 m Above 2000 m with 0.5 % derating per 100 m
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	50 °C
Ambient storage temperature - min	-50 °C
Ambient storage temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-3 Damp heat, cyclic, to IEC 60068-2-30

Main conducting paths

Overload cycle	AC-53a: 4.0 - 32: 99 - 3
Rated operational current (Ie) at AC-53	180 A
Rated operational current (Ie) at AC-53, in-delta	311 A
Rated operational voltage (Ue) - min	200 V
Rated operational voltage (Ue) - max	600 V
Short-circuit protection rating	NZMN2-S200, Type “1” coordination, Main conducting paths
Supply frequency	50/60 Hz, fLN, Main circuit
Voltage rating - max	600 V

Motor rating

Assigned motor power at 200/208 V, 60 Hz, 3-phase	60 HP
Assigned motor power at 220/230 V, 60 Hz, 3-phase	60 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase	150 HP
Assigned motor power at 600 V, 60 Hz, 3-phase	150 HP
Assigned motor power in-delta at 220/230 V, 60 Hz	100 HP
Assigned motor power in-delta at 460/480 V, 60 Hz	250 HP
Assigned motor power in-delta at 575/600 V, 60 Hz	300 HP
Rated operational power at 220/230 V, 50 Hz	55 kW
Rated operational power at 400 V, 50 Hz	90 kW
Rated operational power at 500 V, 50 Hz	110 kW
Rated operational power in-delta at 220/230 V, 50 Hz	90 kW
Rated operational power in-delta at 400 V, 50 Hz	160 kW
Rated operational power in-delta at 500 V, 50 Hz	200 kW

Terminal capacities

Terminal capacity (flexible with ferrule)	1 x (70 - 240) mm^2, Main cables 2 x (1 - 2.5) mm^2, Control circuit cables 2 x (25 - 240) mm^2, Main cables 1 x (2.5 - 4) mm^2, Control circuit cables
Terminal capacity (solid)	1 x (70 - 240) mm^2, Main cables 2 x (1 - 2.5) mm^2, Control circuit cables 1 x (2.5 - 4) mm^2, Control circuit cables 2 x (25 - 240) mm^2, Main cables
Terminal capacity (solid/stranded AWG)	2 x (4 - 500 kcmil), Main cables 1 x (4 - 500 kcmil), Main cables 2 x (14 - 12), Control circuit cables 1 x (14 - 12), Control circuit cables
Terminal capacity (stranded)	1 x (70 - 240) mm^2, Main cables 1 x (2.5 - 4) mm^2, Control circuit cables 2 x (25 - 240) mm^2, Main cables

	2 x (1 - 2.5) mm^2, Control circuit cables
Screwdriver size	4 mm Hexagon socket-head screw, Terminal screw, Main cables 0.6 x 3.5 mm, Terminal screws, Control circuit cables
Tightening torque	28.3 Nm (> 150 mm^2) 0.4 Nm, Screw terminals, Control circuit cables 25.5 Nm (≤ 150 mm^2)
Control circuit	
Current consumption	150 mA, Control circuit, Digital inputs, External 24 V 100 mA, Control circuit, Digital inputs, External 24 V (no-load) 10 A/150 ms, Control circuit, Regulator supply at peak performance (close bypass) at 24 V DC 1000 mA, Control circuit, Regulator supply
Drop-out time	100 ms, DC operated
Drop-out voltage	0 - 3 V, DC operated
Pick-up time	100 ms at DC
Pick-up voltage	21.6 - 26.4 V DC
Rated control supply voltage (Us) at AC, 50 Hz - min	0 V
Rated control supply voltage (Us) at AC, 50 Hz - max	0 V
Rated control supply voltage (Us) at AC, 60 Hz - min	0 V
Rated control supply voltage (Us) at AC, 60 Hz - max	0 V
Rated control supply voltage (Us) at DC - min	24 V
Rated control supply voltage (Us) at DC - max	24 V
Input/Output	
Input current	4 - 20 mA (Analog inputs)
Number of inputs	1 (current input)
Number of outputs	2 Relay Outputs (programmable)
Output voltage	120 V AC/DC (relay outputs)
Protection	Finger and back-of-hand proof, Protection against direct contact
Rated control voltage (Uc)	24 V DC (-10 %/+10 %) 24 V DC
Rated operational current (Ie) at AC-11	3 A
Soft start function	
Application	Soft starting of three-phase asynchronous motors 3-phase motors: Yes
Delay time	0 - 120 s, Soft start function, Ramp times
Kickstart	Max. 2000 ms (Kickstart Duration) 100% (Kickstart voltage)
Ramp/run-up time	360 s
Start voltage	Max. 85 %, Soft start function, Start voltage = turn-off voltage
Design verification	
Equipment heat dissipation, current-dependent Pvid	25 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	180 A
Static heat dissipation, non-current-dependent Pvs	25 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Soft starter (EC000640)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Load breakout, motor breakout / Semiconductor motor controller or soft starter (ecl@ss13-27-37-09-07 [ACO300016])			
Rated operation current Ie at 40 °C Tu		A	180
Rated operating voltage Ue		V	200 - 600
Rated power three-phase motor, inline, at 230 V		kW	55
Rated power three-phase motor, inline, at 400 V		kW	90
Rated power three-phase motor, inside delta, at 230 V		kW	90
Rated power three-phase motor, inside delta, at 400 V		kW	160
Function			Single direction
Internal bypass			Yes
With display			Yes
Torque control			No
Rated surrounding temperature without derating		°C	50
Rated control supply voltage AC 50 Hz		V	0 - 0
Rated control supply voltage AC 60 Hz		V	0 - 0
Rated control supply voltage DC		V	24 - 24
Voltage type for actuating			DC
Integrated motor overload protection			Yes
Release class			Adjustable
Degree of protection (IP)			IP20
Degree of protection (NEMA)			Other

© 04/2023 by Eaton Industries GmbH