# KERN **KFD 600V20LM**

Weighing bridge made of non-slip corrugated steel plate, lacquered



## Category

| | |
|---|---|
| Brand | KERN |
| Product category | Component |
| Product group | Weighing bridge |
| Product family | KFD-V20-IP67 |

## Measuring System

| | |
|---|---|
| Weighing capacity [Max] | 600 kg |
| Readability [d] | 200 g |
| Minimum weight [Min] (verifiable) | 4 kg |
| Load cell connection | 6-wire |
| Loadcell type | ZEMIC H8C 0.5 ton |

## Construction

| | |
|---|---|
| Dimensions weighing surface (W×D) | 1200×1200 mm |
| Dimensions weighing surface | 1200×1200 mm |
| Dimensions weighing platform (W×D×H) | 1800×1420×95 mm |
| Material weighing plate | steel, powder-coated |
| Material platform | steel, powder-coated |
| Material load cell(s) | alloyed steel |
| Material substructure | steel, powder-coated |
| Levelling feet adjustable | ✓ |
| Cable length | 5 m |
| Platform Construction | Welded load plate; chequer plate |
| Load cells - number | 4 |
| Nominal load capacity (WLL) | 2250 kg |

## Functions

| | |
|---|---|
| IP protection - platform | IP67 |
| IP protection - load cell | IP67 |

## Approval

| | |
|---|---|
| Conformity assessment possible ex works | ✓ |
| Verification scale interval [e] | 200 g |

## Services (optional)

| | |
|---|---|
| Article number for conformity assessment | 965-230 |
| Article number for DAkkS calibration | 963-130 |

## Packing & Shipping

| | |
|---|---|
| Delivery time | 2 d |
| Dimensions packaging (W×D×H) | 1860×1520×370 mm |
| Shipping method | Freight |
| Net weight approx. | 165 kg |
| Gross weight approx. | 245 kg |
| Shipping weight | 245 kg |
| Shipping volume weight | 209,2 kg |

## Product information

| | |
|---|---|
| GTIN/EAN number | 4045761493674 |
| Trade number | 90318080 |
| REACH classification | no prohibited substances |

## Pictograms

### STANDARD




### FACTORY

